


RENOVATIONS OF BAYWOOD TECHNOLOGY & COMMUNITY CENTER

247 Grammer Lane
Baywood, VA. 24333


10/25/2021 - CONSTRUCTION DOCUMENTS



ABBREVIATIONS			ABBREVIATIONS			ABBREVIATIONS			ABBREVIATIONS		
Abbreviation	ABBREV	TERM	Abbreviation	ABBREV	TERM	Abbreviation	ABBREV	TERM	Abbreviation	ABBREV	TERM
A	&, +	AND	D	DWR	DRAWER	K	KSF	KIPS PER SQUARE FOOT	R	RTU	ROOF TOP UNIT
A	@	AT	E	E	EAST	L	LAM	LAMINATE	S	S	SOUTH
A	A/C	AIR CONDITIONING	E	EA	EACH	L	LAV	LAVATORY	S	SA	SUPPLY AIR
A	AV	AUDIO/VISUAL	E	EB	EXPANSION BOLT	L	LB	POUNDS	S	SAF	SELF-ADHERED FLASHING
A	AB	ANCHOR BOLT	E	EJ	EXPANSION JOINT	L	LGMS	LIGHT GAUGE METAL STUD	S	SCHED	SCHEDULE
A	ACC	ACCESSIBLE	E	EL	ELEVATION	L	LH	LONG LEG HORIZONTAL	S	SCW	SOLID CORE WOOD
A	ACoust	ACOUSTICAL	E	ELEC	ELECTRICAL	L	LLV	LONG LEG VERTICAL	S	SD	STORM DRAIN
A	ACT	ACOUSTIC CEILING TILE	E	ELEV	ELEVATOR, ELEVATION	L	LT	LIGHT	S	SECT	SECTION
A	AD	AREA DRAIN	E	EMER	EMERGENCY	L	LVT	LUXURY VINYL TILE	S	SF	SQUARE FEET; SQUARE FOOT
A	ADJ	ADJACENT, ADJUSTABLE	E	ENCL	ENCLOSURE	M	M	MASONRY	S	SH	SPRINKLER HEAD
A	AFF	ABOVE FINISHED FLOOR	E	ENGR	ENGINEER	M	MAS	MASONRY	S	SHR	SHOWER
A	AFG	ABOVE FINISHED GRADE	E	EP	ELECTRICAL PANEL	M	MAX	MAXIMUM	S	SHT	SHEET
A	AGGR	AGGREGATE	E	EPDM	ETHYLENE PROPYLENE DIENE M-CLASS (ROOFING)	M	MB	MODIFIED BITUMEN (ROOFING)	S	SIM	SIMILAR
A	ALT	ALTERNATE	E	EQ	EQUAL	M	MECH	MECHANICAL	S	SM	SHEET METAL; SURFACE-MOUNTED
A	ALUM	ALUMINUM	E	EQUIP	EQUIPMENT	M	MED	MEDIUM	S	SP	STANDPIPE
A	ANOD	ANODIZED	E	EXH	EXHAUST	M	MEMB	MEMBRANE	S	SPC	SPECIFICATION; SPECIFIED
A	APC	ACOUSTICAL PANEL CEILING	E	EXST	EXISTING	M	MFR	MANUFACTURER	S	SPK	SPRINKLER OR SPEAKER
A	APPROX	APPROXIMATE	E	EXP	EXPANSION	M	MH	MANHOLE	S	SPKR	SPEAKER
A	ARCH	ARCHITECTURAL	E	EXT	EXTERIOR	M	MIN	MINIMUM	S	SQ	SQUARE
A	ASPH	ASPHALT	F	F	FIRE ALARM	M	MISC	MISCELLANEOUS	S	SS	STAINLESS STEEL
A	ATTN	ATTENTION	F	FA	FIRE ALARM	M	MO	MASONRY OPENING	S	SSK	SERVICE SINK
A	AUTO	AUTOMATIC	F	FB	FACE BRICK	M	MR	MOISTURE RESISTANT	S	STA	STATION
B	BCAB	BASE CABINET	F	FD	FLOOR DRAIN; FIRE DEPARTMENT	M	MTD	MOUNTED	S	STC	SOUND TRANSMISSION COEFFICIENT
B	BD	BOARD	F	FDC	FIRE DEPARTMENT CONNECTION	M	MTG	MOUNTING	S	STL	STEEL
B	BG	BUMPER GUARD	F	FE	FIRE EXTINGUISHER	M	MTL	METAL	S	STOR	STORAGE
B	BIT	BITUMINOUS	F	FEC	FIRE EXTINGUISHER CABINET	M	MULL	MULLION	S	STRG	STRINGER
B	BL	BEL LOCATOR; BUILDING LINE	F	FFBE	FURNITURE, FIXTURES AND EQUIPMENT	N	N	NORTH	S	STRUCT	STRUCTURE; STRUCTURAL
B	BLDG	BUILDING	F	FFB	FINISH FLOOR BOX	N	N/A	NOT APPLICABLE	S	SUBCAT	SUBCATEGORY
B	BLK	BLOCK	F	FFE	FINISH FLOOR ELEVATION	N	NC	NOISE CRITERIA	S	SUSP	SUSPENDED
B	BLKG	BLOCKING	F	FH	FLAT HEAD, FIRE HYDRANT	N	NC	NOISE CRITERIA	S	SYM	SYMMETRICAL
B	BM	BEAM	F	FHC	FIRE HOSE CABINET	N	NIC	NOT IN CONTRACT	S	SYS	SYSTEM
B	BO	BOTTOM OF	F	FIN	FINISH	N	NO	NUMBER	T	T	TREAD
B	BOT	BOTTOM	F	FIXT	FIXTURE	N	NOM	NOMINAL	T	T&B	TOP AND BOTTOM
B	BRG	BEARING	F	FLASH	FLASHING	N	NTS	NOT TO SCALE	T	T&G	TONGUE AND GROOVE
B	BRK	BRICK	F	FLR	FLOOR	O	O.C	OWNER-FURNISHED, CONTRACTOR-INSTALLED	T	TB	TOWEL BAR
B	BRKT	BRACKET	F	FLUOR	FLUORESCENT	O	O.D	OWNER-FURNISHED, OWNER-INSTALLED	T	TEL	TELEPHONE; TELECOM
B	BSMT	BASEMENT	F	FND	FOUNDATION	O	O/C	ON CENTER	T	TELE	TELEPHONE
B	BUR	BUILT-UP ROOFING	F	FO	FACE OF	O	OA	OUTSIDE AIR	T	TEMP	TEMPERATURE, TEMPORARY
C	C	CHANNEL	F	FP	FIRE PROTECTION	O	OD	OUTSIDE DIAMETER, OVERFLOW DRAIN	T	TEMP	TEMPORARY
C	C.C	CONTRACTOR-FURNISHED, CONTRACTOR-INSTALLED	F	FPF	FIREPROOFING	O	OD	OVERFLOW DRAIN	T	THK	THICKNESS
C	CAB	CABINET	F	FR	FIRE RESISTANT	O	OFF	OFFICE	T	THRU	THROUGH
C	CAT	CATEGORY	F	FRP	FIBER REINFORCED CONCRETE	O	OH	OVERHEAD	T	TKBD	TACK BOARD
C	CATV	CABLE TELEVISION	F	FRP	FIBER REINFORCED PANEL	O	OPNG	OPENING	T	TLT	TOILET
C	CB	CATCH BASIN, CEMENT BOARD	F	FRT	FIRE RETARDANT TREATED	O	OPP	OPPOSITE	T	TMPD	TEMPERED
C	CBU	CEMENTITIOUS BACKER UNIT	F	FT	FEET; FOOT	O	ORD	OVERFLOW ROOF DRAIN	T	TO	TOP OF
C	CC	CENTER-TO-CENTER	F	FTG	FOOTING	P	P	PAINT	T	TOB	TOP OF BEAM
C	CCTV	CLOSED-CIRCUIT TELEVISION	F	FUR	FURNITURE	P	PAV	PAVING	T	TOC	TOP OF CONCRETE
C	CEM	CEMENT	F	FURR	FURRING	P	PB	PARTICLE BOARD	T	TOS	TOP OF STEEL
C	CER	CERAMIC	F	FWC	FABRIC WALL COVERING	P	PC	PRECAST	T	TV	TELEVISION
C	CG	CORNER GUARD	F	FWP	FABRIC WRAPPED PANEL	P	PDF	POWER DRIVEN FASTENER	T	TYP	TYPICAL
C	CH	CHILLER	G	GA	GAUGE	P	PEFB	PRE-ENGINEERED METAL BUILDING	U	UNFIN	UNFINISHED
C	CI	CAST-IRON	G	GAUV	GALVANIZED	P	PERF	PERFORATED	U	UNO	UNLESS NOTED OTHERWISE
C	CIP	CAST-IN-PLACE	G	GB	GRAB BAR	P	PERM	PERIMETER	U	UNO	UNLESS NOTED OTHERWISE
C	CI	CONTROL JOINT, CONSTRUCTION JOINT	G	GB, GWB	GYPSUM (WALL) BOARD	P	PERP	PERPENDICULAR	U	URNL	UNLESS OTHERWISE NOTED
C	CL	CENTERLINE	G	GC	GENERAL CONTRACTOR	P	PL	PLATE	V	VAR	VARIES
C	CLG	CEILING	G	GEN	GENERAL	P	PLAM	PLASTIC LAMINATE	V	VCT	VINYL COMPOSITION TILE
C	CLR	CLEAR	G	GFRC	GLASS FIBER REINFORCED CONCRETE	P	PLAS	PLASTER	V	VERT	VERTICAL
C	CMU	CONCRETE MASONRY UNIT	G	GLZ	GLAZING	P	PLBG	PLUMBING	V	VEST	VESTIBULE
C	CNTR	CENTER, COUNTER	G	GLN	GLAZING	G	PLF	POUNDS PER LINEAL FOOT	V	VIF	VERIFY IN FIELD
C	CO	CASED OPENING, CLEANOUT	G	GRAN	GRANULAR	G	PLYW	PLYWOOD	V	VP	VISION PANEL
C	COL	COLUMN	G	GRD	GROUND	G	GRFG	GLASS FIBER REINFORCED GYPSUM	V	VW	VAPOR RETARDER
C	CONC	CONCRETE	G	GSM	GALVANIZED SHEET METAL	G	GSM	GALVANIZED SHEET METAL	V	VWC	VINYL WALL COVERING
C	COND	CONDITION	G	GV	GAS VALVE	G	PNT	PAIN'T; PAINTED	W	W	WIDE; WEST
C	CONN	CONNECTION	G	GYP	GYPSUM	G	POL	POLISHED	W	WJ	WITH
C	CONST	CONSTRUCTION	H	H	HIGH	G	PR	PAIR	W	W/O	WITHOUT
C	CONT	CONTINUOUS	H	H, HT	HIGH; HEIGHT	P	PREFAB	PREFABRICATED	W	WC	WATER CLOSET
C	CONTR	CONTRACTOR	H	HB	HOSE BIB	P	PROJ	PROJECT	W	WD	WOOD
C	COORD	COORDINATE	H	HC	ACCESSIBLE	P	PSF	POUNDS PER SQUARE FOOT	W	WIN	WINDOW
C	CORR	CORRIDOR	H	HC	ACCESSIBLE	P	PT	POINT, PRESSURE-TREATED	W	WP	WATERPROOF; WATERPROOFING
C	CPT	CARPET	H	HDWD	HARDWOOD	P	PTD	PAINTED	W	WPM	WATERPROOF MEMBRANE
C	CR	CRASH RAIL	H	HDWR	HARDWARE	P	PTN	PARTITION	W	WS	WEATHER-STRIPPING
C	CSS	CLINICAL SERVICE SINK	H	HGT	HEIGHT	P	PTN	PARTITION	W	WSCT	WEATHER-STRIPPING
C	CT	CERAMIC TILE	H	HM	HOLLOW METAL	Q	QTY	QUANTITY	W	WT	WEIGHT
C	CTR	CENTER	H	HNDRL	HANDRAIL	Q	QTY	QUANTITY	W	WV	WATER VALVE
C	CTS	COUNTERSINK	H	HNDRL	HANDRAIL	R	R	RADIUS, RISER	W	WWF	WELODED WIRE FABRIC
C	CW	COLD WATER, CURTAIN WALL	H	HO	HOLD OPEN	R	RA	RETURN AIR	W	WWM	WELODED WIRE MESH
D	D	DEEP, DEPTH	H	HSS	HOLLOW STRUCTURAL SECTION	R	RAD	RADIUS			
D	DBL	DOUBLE	H	HTG	HEATING	R	RB	RESILIENT BASE			
D	DEG	DEGREE	H	HVAC	HEATING, VENTILATION, AND AIR CONDITIONING	R	RR	RUBBER			
D	DEMO	DEMOLISH; DEMOLITION	H	HW	HOT WATER; HAND WASH	R	RCP	REFLECTED CEILING PLAN			
D	DEPT	DEPARTMENT	I	ID	INSIDE DIAMETER	R	RD	ROOF DRAIN			
D	DF	DRINKING FOUNTAIN	I	IN	INCH; INCHES	R	REC	RECESSED			
D	DIA	DIAMETER	I	INCL	INCLUDED; INCLUDING	R	RECP	RECEPTACLE			
D	DIFF	DIFFUSER	I	INFO	INFORMATION	R	REF	REFERENCE			
D	DIM	DIMENSION	I	INSUL	INSULATED; INSULATION	R	REFR	REFRIGERATOR			
D	DIMS	DIMENSIONS	I	INT	INTERIOR	R	REG	REGISTER			
D	DISP	DISPENSER	I	INT	INTERIOR	R	REIN	REINFORCED; REINFORCING			
D	DIV	DIVISION	I	INV	INVERT	R	RELOC	RELOCATE			
D	DMPP	DAMP PROOFING	J	JAN	JANITOR	R	REM	REMOVABLE			
D	DN	DOWN	J	JAN	JANITOR	R	REQ	REQUIRED; REQUIRED			
D	DO	DOOR OPENING	J	JAN	JANITOR	R	REQD	REQUIRED			
D	DR	DOOR	J	JAN	JANITOR	R	RESIL	RESILIENT			
D	DRN	DRAIN	J	JC	JANITOR'S CLOSET	R	REV	REVISION; REVISED			
D	DS	DOWNSPOUT	J	JST	JOIST	R	RM	ROOM			
D	DTL	DETAIL	K	JT	JOINT	R	RO	ROUGH OPENING			
D	DW	DISHWASHER	K	K	KIP (1000 POUNDS)	R	RTD	RATED			
D	DWG	DRAWING	K	KIT	KITCHEN	R	RTG	RATING			
D	DWMS	DRYWALL METAL STUD	K	KO	KNOCK OUT	R	RTG	RATING			
			K	KP	KICK PLATE						



Renovations of
**Baywood
Technology &
Community Center**
Address
Address



CONTACT INFORMATION

CIVIL
BOWMAN-BUNN
152 N. MAIN ST.
MOUNT AIRY, NC. 27030
PHONE
CONTACT: BROCK BOWMAN, P.E.

MECHANICAL
BEEKMAN POINT ENGINEERING
295 SEVEN FARMS DR.,
STE. C-321
DANIEL ISLAND, SC. 29492
843-471-5488

STRUCTURAL
KNOBELOCH & PADGETT
478 HWY 378 W.
LEXINGTON, SC. 29072
803-808-8020
CONTACT: DAVID PADGETT, P.E.

PLUMBING
BEEKMAN POINT ENGINEERING
295 SEVEN FARMS DR.,
STE. C-321
DANIEL ISLAND, SC. 29492
843-471-5488



ARCHITECTURAL
WM2A ARCHITECTS
403B NORTH MAIN ST.
HILLSVILLE, VA 24343
478-745-4945
CONTACT: YANCEY POWERS, NCARB

ELECTRICAL
BRITTE ENGINEERING
2001 OLD WESTFIELD RD.
PILOT MOUNTAIN, NC. 27041
336-351-5001
MEP CONTACT: JASON WHITE, P.E.

SHEET LIST

Sheet Number	Sheet Name
General	
G0-0	Cover Sheet
LS-1	Life Safety Plan and information
Architecture	
A1-0	Area Plan
A1-1	First Floor Phase 1 Tri-Area Demo and New Work
A1-2	First Floor Phase 1 Community Education Demo and New Work
A2-2	Door Schedule and Details
A2-3	Window Schedule and Details
A3-2	Canopy Details
A4-1A	Wall Types and Details - Metal Framing
A4-1C	Wall Types and Details - Masonry
A5-2	Interior Elevations and Casework Details - Phase 1
A6-1	RCP- Phase 1
A7-1	Finish Plan - Phase 1
A7-2	Equipment Plan - Phase 1, Toilet Accessories, and ADA Legend
Mechanical	
M0-01	HVAC Title Sheet
M1-01	First Floor Phase 1 Overall Mechanical Plan
M1-02	Roof Mechanical Plan
M2-01	First Floor Phase 1 Enlarged Mechanical Plan
M2-02	First Floor Phase 1 Enlarged Mechanical Plan
M5-01	Mechanical Details
M6-01	Mechanical Schedules
Plumbing	
P0-01	Plumbing Title Sheet
P1-01	First Floor Phase 1 Medical Area Plumbing Plan
P1-02	First Floor Phase 1 Restroom Plumbing Plan
P01-01	First Floor Plumbing Demolition Phasing Plan
Electrical	
E-0.1	Electrical Cover Sheet
E-0.2	Electrical Rise Diagram & Electrical Schedules
E-1.0	Overall Lighting Plan
E-1.1	Enlarged Lighting Plans
E-1.2	Enlarged Lighting Plans
E-2.0	Overall Power & Fire Alarm Plan
E-2.1	Enlarged Power & Fire Alarm Plan
E-2.2	Enlarged Power & Fire Alarm Plan
E-3	Roof HVAC Electrical & Power Plan
ED-1	Electrical Demo Plan





LIFE SAFETY LEGEND

- - - - - • 1-HOUR FIRE BARRIER (IBC SEC. 707)
- - - - - • 2-HOUR FIRE BARRIER (IBC SEC. 709)
- ← • PATH OF TRAVEL
- FEC • FIRE EXTINGUISHER CABINET

TABLE 722.2.1.4(2)
TIME ASSIGNED TO FINISH MATERIALS
ON FIRE-EXPOSED SIDE OF WALL

FINISH DESCRIPTION	TIME (minutes)
Gypsum wallboard	
1/2 inch	10
3/8 inch	15
5/8 inch	20
2 layers of 3/8 inch	25
1 layer of 3/8 inch, 1 layer of 1/2 inch	35
2 layers of 1/2 inch	40
Type X gypsum wallboard	
1/2 inch	25
5/8 inch	40
Portland cement-sand plaster applied directly to concrete masonry	See Note a
Portland cement-sand plaster on metal lath	
3/4 inch	20
1/2 inch	25
1 inch	30
Gypsum sand plaster on 3/8-inch gypsum lath	
1/2 inch	35
3/4 inch	40
1 inch	50
Gypsum sand plaster on metal lath	
3/4 inch	50
1 inch	60
1 inch	80

For SI: 1 inch = 25.4 mm.
a. The actual thickness of Portland cement-sand plaster, provided that it is 3/8 inch or less in thickness, shall be permitted to be included in determining the equivalent thickness of the masonry for use in Table 722.3.2.

1 | LIFE SAFETY PLAN

LS-1 | 3/16" = 1'-0"

LIFE SAFETY INFORMATION

BUILDING INFORMATION:
PROJECT NAME: BAYWOOD TECHNOLOGY CENTER
ADDRESS: 247 GRAMMER LANE
BAYWOOD VA
USE: EDUCATION/BUSINESS
OWNER: GRAYSON COUNTY VA

CODE ANALYSIS:

- I. APPLICABLE CODES:
 - INTERNATIONAL FIRE CODE (IFC) (2018), with VA STATE AMENDMENTS
 - VIRGINIA CONSTRUCTION CODE (CBC) (2018), with VA STATE AMENDMENTS
- II. OCCUPANCY TYPE:
 - BUSINESS, GROUP B (VBC 304)
 - ASSEMBLY, GROUP A3 (VBC 303)
 - EDUCATIONAL, GROUP (VBC 305)
- III. EXISTING BUILDING CONSTRUCTION TYPE:
 - TYPE III (IBC TABLE 603)
- IV. BUILDING AREA:
 - ACTUAL: 2 STORIES @ 22,790 SF (VBC TABLE 504)
 - ALLOWED: 2 STORY @ 9,500 ALLOWED A3, 19,000 ALLOWED B, 14,500 ALLOWED E (VBC TABLE 504)
- V. HOURLY FIRE RATINGS (IBC TABLE 601):
 - STRUCTURAL FRAME: 0 HOURS
 - BEARING WALLS, EXT.: 0 HOURS
 - BEARING WALLS, INT.: 0 HOURS
 - NON-BEARING WALLS, EXT.: 0 HOURS
 - NON-BEARING WALLS, INT.: 0 HOURS
 - FLOOR CONSTRUCTION: 0 HOURS
 - ROOF CONSTRUCTION: 0 HOURS
- VI. FIRE SUPPRESSION SYSTEM:
 - PORTABLE FIRE EXTINGUISHERS
- VII. RENOVATION AREA:
 - 1 STORY @ 8,654 GSF TOTAL
- VIII. FIRE SAFETY CONCEPT:
 - EXISTING EDUCATIONAL BUILDING TO REMAIN AS IS. NEW BUSINESS OCCUPANCY TO BE SEPARATED FROM REMAINING EDUCATIONAL SPACE BY 2 HR WALLS PER 508.4 ENTIRE FACILITY TO RECEIVE NEW FIRE ALARM PER VBC 907.2.3

- IX. OTHER LIFE SAFETY CONSIDERATIONS (MOST STRINGENT OF APPLICABLE CODES GOVERNS):
 - A. OCCUPANT LOAD: (IBC TABLE 1004.5)
 - BUSINESS OFFICE: 2,661 GSF
150 GSF/OCCUPANT = 18 OCCUPANTS
 - EXISTING EDUCATION MAIN FLOOR: 3 CLASSROOMS 2,390 SF
20 GSF/OCCUPANT = 119.5 OCCUPANTS
 - EXISTING EDUCATION 2ND FLOOR: 6 CLASSROOMS 5,489 SF
20 GSF/OCCUPANT = 275 OCCUPANTS
 - EXISTING A3 ASSEMBLY: 3,112 GSF
15 GSF/OCCUPANT = 208 OCCUPANTS
 - EXISTING KITCHEN: 1,200 GSF
200 GSF/OCCUPANT = 7 OCCUPANTS
TOTAL = 625 OCCUPANTS
 - B. EXIT DOOR CAPACITY (VBC TABLE 1005.1.)
 - 0-2" EGRESS WIDTH PER OCCUPANT SERVED IN UNSPRINKLERED FACILITY
SEE LIFE SAFETY PLAN FOR REQUIRED AND PROVIDED EGRESS WIDTHS
 - C. DEAD END (VBC 1017.3) = 20 FEET
NONE PROVIDED
 - E. TRAVEL DISTANCE (VBC TABLE 1017.2) = 250 FEET ALLOWABLE
MAXIMUM ACTUAL EXIT DISTANCE = 108.86'
 - F. INTERIOR FINISH
 - 1. INTERIOR WALL AND CEILING FINISH (VBC TABLE 803.5.)
INTERIOR WALL AND CEILING FINISH COMPLYING WITH 10.2.3 SHALL BE AT A MINIMUM REQUIREMENT CLASS A IN EXIT ENCLOSURES AND PASSAGEWAYS, CLASS B IN CORRIDORS, AND CLASS C IN OFFICE AREAS.
 - 2. INTERIOR FLOOR FINISH (VBC 804.4.1) - CLASS I

TABLE 722.4.1(1)
FIRE-RESISTANCE PERIODS OF CLAY MASONRY WALLS

MATERIAL TYPE	MINIMUM REQUIRED EQUIVALENT THICKNESS FOR FIRE RESISTANCE ^{a, b, c} (inches)			
	1 hour	2 hours	3 hours	4 hours
Solid brick of clay or shale ^d	2.7	3.8	4.9	6.0
Hollow brick or tile of clay or shale, unfilled	2.3	3.4	4.3	5.0
Hollow brick or tile of clay or shale, grouted or filled with materials specified in Section 722.4.1.1.3	3.0	4.4	5.5	6.6

For SI: 1 inch = 25.4 mm.
a. Equivalent thickness as determined from Section 722.4.1.1.
b. Calculated fire resistance between the hourly increments listed shall be determined by linear interpolation.
c. Where combustible members are framed in the wall, the thickness of solid material between the end of each member and the opposite face of the wall, or between members set in from opposite sides, shall be not less than 93 percent of the thickness shown.
d. For units in which the net cross-sectional area of cored brick in any plane parallel to the surface containing the cores is not less than 75 percent of the gross cross-sectional area measured in the same plane.

TABLE 722.2.2.1
MINIMUM SLAB THICKNESS (inches)


CONCRETE TYPE	FIRE-RESISTANCE RATING (hours)				
	1	1 1/2	2	3	4
Siliceous	3.5	4.3	5	6.2	7
Carbonate	3.2	4	4.6	5.7	6.6
Sand-lightweight	2.7	3.3	3.8	4.6	5.4
Lightweight	2.5	3.1	3.6	4.4	5.1

For SI: 1 inch = 25.4 mm.

PARTITION TYPE LEGEND

<p>WALL TYPES</p> <p>C CMU (MAY HAVE FURRING)</p> <p>G GYPSUM BOARD WITH METAL STUDS</p> <p>S SHAFTWALL</p> <p>W GYPSUM BOARD WITH WOOD STUDS</p>	<p>WALL TYPE</p> <p>STUD/CMU WIDTH</p> <p>WALL TYPE MODIFIER</p> <p>FIRE RATING OR PARTITION HEIGHT</p>	<p>SYMBOL DESIGNATION</p> <p>FOR WALL TYPES INDICATED TO RECEIVE SOUND ATTENUATION, EXTEND SOUND ATTENUATION TO FULL HEIGHT OF WALL UNLESS OTHERWISE INDICATED. REFER TO INDIVIDUAL WALL TYPE MODIFIER FOR STC RATINGS.</p> <p>WITH SOUND ATTENUATION</p> <p>NO SOUND ATTENUATION</p>	<p>WALL HATCH PATTERN LEGEND</p> <p>NON-RATED METAL STUD PARTITION</p> <p>NON-RATED SMOKE PARTITION</p> <p>1 HOUR RATED FIRE PARTITION</p> <p>2 HOUR RATED FIRE BARRIER</p> <p>1 HOUR RATED FIRE/SMOKE BARRIER</p> <p>2 HOUR RATED FIRE/SMOKE BARRIER</p> <p>NON-RATED MASONRY</p> <p>1 HOUR RATED MASONRY FIRE BARRIER (ULIF U90S)</p> <p>2 HOUR RATED MASONRY FIRE BARRIER (ULIF U90S)</p>
--	--	--	---

LEGEND - WALL TYPES - HORIZONTAL





ARCHITECTS
WM2A.COM
 403B NORTH MAIN ST
 HILLSVILLE, VA 24343





Renovations of
**Baywood
 Technology &
 Community Center**
 Address
 Address



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
 © 2021, WM2A Architects/Planners, Inc.
 (5/15) WM2A Architects
 These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.
 Project Status: Working Drawings
 Revision No. (if any): Revision Date:
 Project No.: 2021-003 Current Date: 10/25/21
 Drawing Name: Area Plan




1 | Floor Plan - Level 1 Area Plan
 A1-0 | 3/16" = 1'-0"



1 First Floor Plan - Phase 1.1 Demolition
A1-1 1/4" = 1'-0"

NO.	DESCRIPTION
1	DEMOLISH EXISTING WALL
2	EXISTING PLUMBING FIXTURE TO BE DEMOLISHED. CAP LINES AS REQUIRED.
3	EXISTING DOOR AND FRAME TO BE DEMOLISHED.
4	DEMOLISH EXISTING WALL TO 3'-4.5" AFF.
5	REMOVE EXISTING LIGHTING
6	REMOVE EXISTING FLOORING. PREP FOR NEW.
7	DEMOLISH EXISTING TOILET PARTITIONS
8	SAW-CUT EXISTING SLAB. COORDINATE WITH MEP PLAN.
9	REMOVE EXISTING QUARRY TILE. REMOVE SETTING BED.



2 First Floor Plan - Phase 1.1 New Work
A1-1 1/4" = 1'-0"

NO.	DESCRIPTION
1	ALIGN NEW WALL WITH EXISTING
2	INFILL WALL TO MATCH EXISTING CONSTRUCTION.
3	PROVIDE SOUND SEALS FOR DOOR.
4	REMOTE WATER SHUT OFF
5	PROVIDE WINDOW SPEAKER
6	INSTALL NEW PLUMBING FIXTURES
7	INSTALL NEW CASEWORK
8	PROVIDE 4X8 SHEET OF DEDICATED PLYWOOD FOR MOUNTING DATA EQUIPMENT
9	PREPARE ROOM FOR NEW FINISHES, AND INSTALL NEW FINISHES AS SCHEDULED.

NO.	DESCRIPTION
10	INSTALL EQUIPMENT AND ACCESSORIES
11	PROVIDE NEW DOOR SIGNAGE
12	INSTALL NEW PASS THROUGH CABINET.
13	INSTALL NEW COOKSON (TM) MOTOR OPERATED, BRICK PATTERN, ROLLING GRILLE, WALL MOUNTED SECURITY GATE ABOVE CEILING AT PHARMACY WINDOW. SECURITY GATE TO COVER THE ENTIRE GLAZING SYSTEM. SEE MANUFACTURER SPECIFICATIONS FOR MOUNTING INSTRUCTIONS AND CEILING SPACING REQUIREMENTS
14	INSTALL NEW ADA HI-LO DRINKING FOUNTAIN
15	INSTALL NEW TOPPING COAT, AND INSTALL NEW LVT

DEMOLITION NOTES

- OWNER IS RESPONSIBLE FOR REMOVING ANY FURNITURE PRIOR TO CONSTRUCTION
- DEMOLITION PLAN IS NOT ALL INCLUSIVE. ADDITIONAL DEMOLITION WORK MAY BE REQUIRED FOR INSTALLING NEW WORK. SEE MECHANICAL, PLUMBING AND ELECTRICAL DWGS FOR DEMOLITION IN THOSE TRADES. IN AREAS OR ROOMS WHERE ARCHITECTURAL DEMOLITION IS NOT INDICATED AND MECHANICAL, PLUMBING AND ELECTRICAL IS REQUIRED, REMOVE AND REPAIR ANY ITEMS TO ACCOMMODATE WORK REQUIRED AND RESTORE AREA TO ORIGINAL CONDITIONS BEFORE WORK PROCEEDS.
- PROTECT ALL EXISTING CONDITIONS THAT ARE TO REMAIN, AS NECESSARY, DURING DEMOLITION PHASE OF CONSTRUCTION. REPAIR ALL DAMAGE PROMPTLY TO ORIGINAL CONDITION.
- DEMOLITION SHALL INCLUDE ANY REMOVAL OF EXISTING MATERIALS TO MAKE PROVISION FOR NEW FINISHES.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL EXISTING CONDITIONS. THE ARCHITECT IS TO BE NOTIFIED OF ANY DISCREPANCIES AND ANY DISCREPANCIES RECTIFIED BEFORE WORK IS TO RESUME.
- ALL STRUCTURAL ITEMS THAT SEEM TO BE SUSPECT FOR REPLACEMENT SHALL BE INSPECTED BY THE PROJECT ARCHITECT OR STRUCTURAL ENGINEER TO DETERMINE IF THEY SHOULD BE REPLACED. ALL STRUCTURAL ITEMS THAT ARE DAMAGED AND NEED REPLACING WILL BE TAGGED BY THE STRUCTURAL ENGINEER AND REPLACED BY THE CONTRACTOR BEFORE ANY OTHER WORK BEGINS.
- ALL DEMOLITION WORK SHALL BE EXECUTED IN A CAREFUL AND ORDERLY MANNER WITH THE LEAST POSSIBLE NOISE, DUST AND DISTURBANCE TO THE OTHER TENANTS.
- THE CONTRACTOR SHALL MAINTAIN AT ALL TIMES ALL EXISTING ACCESS AND FIRE PROTECTION SYSTEMS.
- THE CONTRACTOR SHALL AT ALL TIMES KEEP ALL EXISTING ACCESS/ EGRESS PATHWAYS FREE AND CLEAR OF DEBRIS.


GENERAL FLOOR PLAN NOTES

- CONTRACTOR TO INSTALL ADA ROOM SIGNAGE AT ALL RESTROOMS, JANITORS CLOSETS, SOILED UTILITY ROOMS, AND OTHER NOTED LOCATIONS. CONTRACTOR TO VERIFY WITH OWNER SIGNAGE TYPE.
- CONTRACTOR TO PAINT ALL EXTERIOR DOORS AND FRAMES AN EXTERIOR GRADE, SEMI-GLOSS PAINT - COLOR: SHERWIN WILLIAMS GAUNTLET GRAY SW 7055.
- CONTRACTOR TO CLEAN AND RE-TOUCH UP THE FINISH AS NEEDED OF ALL PHASE 1 EXISTING TO REMAIN INTERIOR DOORS.

PARTITION TYPE LEGEND

WALL TYPES	WALL TYPE	SYMBOL DESIGNATION	WALL HATCH PATTERN LEGEND
C CMU (MAY HAVE FURRING)	WALL TYPE	FOR WALL TYPES INDICATED TO RECEIVE SOUND ATTENUATION, EXTEND SOUND ATTENUATION TO FULL HEIGHT OF WALL UNLESS OTHERWISE INDICATED. REFER TO INDIVIDUAL WALL TYPE MODIFIER FOR STC RATINGS.	NON-RATED METAL STUD PARTITION
G GYPSUM BOARD WITH METAL STUDS	WALL TYPE MODIFIER		NON-RATED SMOKE PARTITION
S SHEETWALL	FIRE RATING OR PARTITION HEIGHT		1 HOUR RATED FIRE PARTITION
W GYPSUM BOARD WITH WOOD STUDS			2 HOUR RATED FIRE BARRIER
			1 HOUR RATED FIRE/SMOKE BARRIER
			2 HOUR RATED FIRE/SMOKE BARRIER
			NON RATED MASONRY
			1 HOUR RATED MASONRY FIRE BARRIER (ULR U905)
			2 HOUR RATED MASONRY FIRE BARRIER (ULR U905)

LEGEND - WALL TYPES - HORIZONTAL
1 1/2" = 1'-0"



5 First Floor Plan - Phase 1 Tri-Area Key Plan
A1-1 1" = 30'-0"


Renovations of
**Baywood
Technology &
Community Center**
Address
Address



These drawings contain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WM2A Architects/Planners, Inc. (5/15/21) WM2A Architects
These drawings, as instruments of service, remain the property of the architect. Unauthorized use or reproduction is prohibited.

Project Status: Working Drawings
Revision No. (if any): Revision Date: 2021-003 10/25/21
Project No.:
Drawing Name: First Floor Phase 1 Tri-Area Demo and New Work
Drawing No.: A1-1



Renovations of
**Baywood
Technology &
Community Center**

Address
Address



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WM2A Architects/Engineers, Inc.
05/21 WM2A Architects
These drawings, as instruments of service, remain the property of the architect. Unauthorized use or reproduction is forbidden.


Project Status: Working Drawings
Revision No (if any): Revision Date:
Project No: 2021-003 Current Date: 10/25/21
Drawing Name: First Floor Plan Phase 1 Community Education Demo and New Work
Drawing No: A1-2

DEMOLITION NOTES


- OWNER IS RESPONSIBLE FOR REMOVING ANY FURNITURE PRIOR TO CONSTRUCTION.
- DEMOLITION PLAN IS NOT ALL INCLUSIVE. ADDITIONAL DEMOLITION WORK MAY BE REQUIRED FOR INSTALLING NEW WORK. SEE MECHANICAL, PLUMBING AND ELECTRICAL DWGS FOR DEMOLITION IN THOSE TRADES. IN AREAS OR ROOMS WHERE ARCHITECTURAL DEMOLITION IS NOT INDICATED AND MECHANICAL, PLUMBING AND ELECTRICAL IS REQUIRED, REMOVE AND REPAIR ANY ITEMS TO ACCOMMODATE WORK REQUIRED AND RESTORE AREA TO ORIGINAL CONDITIONS BEFORE WORK PROCEEDS.
- PROTECT ALL EXISTING CONDITIONS THAT ARE TO REMAIN, AS NECESSARY, DURING DEMOLITION PHASE OF CONSTRUCTION. REPAIR ALL DAMAGE PROMPTLY TO ORIGINAL CONDITION.
- DEMOLITION SHALL INCLUDE ANY REMOVAL OF EXISTING MATERIALS TO MAKE PROVISION FOR NEW FINISHES.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFICATION OF ALL EXISTING CONDITIONS. THE ARCHITECT IS TO BE NOTIFIED OF ANY DISCREPANCIES AND ANY DISCREPANCIES RECTIFIED BEFORE WORK IS TO RESUME.
- ALL STRUCTURAL ITEMS THAT SEEM TO BE SUSPECT FOR REPLACEMENT SHALL BE INSPECTED BY THE PROJECT ARCHITECT OR STRUCTURAL ENGINEER TO DETERMINE IF THEY SHOULD BE REPLACED. ALL STRUCTURAL ITEMS THAT ARE DAMAGED AND NEED REPLACING WILL BE TAGGED BY THE STRUCTURAL ENGINEER AND REPLACED BY THE CONTRACTOR BEFORE ANY OTHER WORK BEGINS.
- ALL DEMOLITION WORK SHALL BE EXECUTED IN A CAREFUL AND ORDERLY MANNER WITH THE LEAST POSSIBLE NOISE, DUST AND DISTURBANCE TO THE OTHER TENANTS.
- THE CONTRACTOR SHALL MAINTAIN AT ALL TIMES ALL EXISTING SMOKE AND FIRE PROTECTION SYSTEMS.
- THE CONTRACTOR SHALL AT ALL TIMES KEEP ALL EXISTING ACCESS/ EGRESS PATHWAYS FREE AND CLEAR OF DEBRIS.

KEYNOTES - DEMOLITION - FLOOR PLANS

NO.	DESCRIPTION
1	DEMOLISH EXISTING WALL
2	EXISTING PLUMBING FIXTURE TO BE DEMOLISHED. CAP LINES AS REQUIRED.
3	EXISTING DOOR AND FRAME TO BE DEMOLISHED.
4	DEMOLISH EXISTING WALL TO 3'-4.5" AFF.
5	REMOVE EXISTING LIGHTING
6	REMOVE EXISTING FLOORING. PREP FOR NEW.
7	DEMOLISH EXISTING TOILET PARTITIONS
8	SAWCUT EXISTING SLAB. COORDINATE WITH MEP PLAN.
9	REMOVE EXISTING QUARRY TILE. REMOVE SETTING BED.



1 First Floor Plan - Phase 1 Community Education Demolition
A1-2 1/4" = 1'-0"



2 First Floor Plan - Phase 1 Community Education New Work
A1-2 1/4" = 1'-0"

KEYNOTES - NEW WORK - FLOOR PLANS

NO.	DESCRIPTION
1	ALIGN NEW WALL WITH EXISTING
2	INFILL WALL TO MATCH EXISTING CONSTRUCTION.
3	PROVIDE SOUND SEALS FOR DOOR.
4	REMOTE WATER SHUT OFF
5	PROVIDE WINDOW SPEAKER
6	INSTALL NEW PLUMBING FIXTURES
7	INSTALL NEW CASEWORK
8	PROVIDE 4X8 SHEET OF DEDICATED PLYWOOD FOR MOUNTING DATA EQUIPMENT
9	PREPARE ROOM FOR NEW FINISHES, AND INSTALL NEW FINISHES AS SCHEDULED.
10	INSTALL EQUIPMENT AND ACCESSORIES
11	PROVIDE NEW DOOR SIGNAGE
12	INSTALL NEW PASS THROUGH CABINET.
13	INSTALL NEW COOKSON (TM) MOTOR OPERATED, BRICK PATTERN, ROLLING GRILLE, WALL MOUNTED SECURITY GATE ABOVE CEILING AT PHARMACY WINDOW. SECURITY GATE TO COVER THE ENTIRE GLAZING SYSTEM. SEE MANUFACTURER SPECIFICATIONS FOR MOUNTING INSTRUCTIONS AND CEILING SPACING REQUIREMENTS
14	INSTALL NEW ADA HI-LO DRINKING FOUNTAIN
15	INSTALL NEW TOPPING COAT, AND INSTALL NEW LVT


GENERAL FLOOR PLAN NOTES

- CONTRACTOR TO INSTALL ADA ROOM SIGNAGE AT ALL RESTROOMS, JANITORS CLOSETS, SOILED UTILITY ROOMS, AND OTHER NOTED LOCATIONS. CONTRACTOR TO VERIFY WITH OWNER SIGNAGE TYPE.
- CONTRACTOR TO PAINT ALL EXTERIOR DOORS AND FRAMES AN EXTERIOR GRADE, SEMI-GLOSS PAINT - COLOR: SHERWIN WILLIAMS GAUNTLET GRAY SW 7019.
- CONTRACTOR TO CLEAN AND RE-TOUCH UP THE FINISH AS NEEDED OF ALL PHASE 1 EXISTING TO REMAIN INTERIOR DOORS.


PARTITION TYPE LEGEND

WALL TYPES	WALL TYPE	SYMBOL DESIGNATION	WALL HATCH PATTERN LEGEND
C CMU (MAY HAVE FURRING)	STUD/CMU WIDTH	FOR WALL TYPES INDICATED TO RECEIVE SOUND ATTENUATION, EXTEND SOUND ATTENUATION TO FULL HEIGHT OF WALL UNLESS OTHERWISE INDICATED. REFER TO INDIVIDUAL WALL TYPE MODIFIER FOR STC RATINGS.	NON-RATED METAL STUD PARTITION
G GYPSUM BOARD WITH METAL STUDS	WALL TYPE MODIFIER		NON-RATED SMOKE PARTITION
S SHAFT WALL	FIRE RATING OR PARTITION HEIGHT		1 HOUR RATED FIRE PARTITION
W GYPSUM BOARD WITH WOOD STUDS			2 HOUR RATED FIRE BARRIER
			1 HOUR RATED FIRE/SMOKE BARRIER
			2 HOUR RATED FIRE/SMOKE BARRIER
			NON RATED MASONRY
			1 HOUR RATED MASONRY FIRE BARRIER (UL4 US2)
			2 HOUR RATED MASONRY FIRE BARRIER (UL4 US2)

LEGEND - WALL TYPES - HORIZONTAL
1 1/2" = 1'-0"




3 First Floor Plan - Phase 1 Community Education Key Plan
A1-2 1" = 30'-0"




DOOR SCHEDULE WM2A PHASE 1

OPNG NO	FROM ROOM	TO ROOM	FullWidth	Height	Door Type	Frame Type	Head Dtl	Jamb Dtl	HW SET	Rated Opng	COMMENTS
101	CORRIDOR	WAITING RM	3'-6"	7'-0"	WNG	HM1	HA	JA	HW 1	45	
101a	CORRIDOR	WAITING RM	3'-6"	7'-0"	WD	HM1	CA	JA	HW 2	NR	
102	RECEPTION	TRIAGE	3'-0"	7'-0"	WN2	HM2	CA	JA	HW 2	NR	
104	EXAM 1	CORRIDOR	3'-6"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
105	EXAM 2	CORRIDOR	3'-6"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
106	EXAM 3	CORRIDOR	3'-6"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
107	TELEMED EXAM	CORRIDOR	3'-6"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
108	STOREROOM	CORRIDOR	3'-0"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
109	EVS	CORRIDOR	4'-0"	7'-0"	WD	HM1	HA	JA	HW 4	NR	
110	CORRIDOR	SOILED	3'-0"	7'-0"	WD	HM1	CA	CA	HW 7	45	
111	CORRIDOR	STAFF TLT	3'-0"	7'-0"	WD	HM1	HA	JA	HW 5	NR	
112	CHECK-IN	CORRIDOR	3'-0"	7'-0"	WN3	HM3	HA	JA	HW 1	45	
112a	CHECK-IN	PHARMACY	3'-0"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
113a	CORRIDOR	CORRIDOR	4'-0"	7'-0"	CO	HM2	CB	CB	HW 3	NR	
114	CORRIDOR	PHARMACY	3'-0"	7'-0"	WN3	HM3	HA	JA	HW 2	NR	
115	BREAKROOM	CORRIDOR	3'-0"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
116	DATA	STOREROOM	3'-0"	7'-0"	WD	HM1	HA	JA	HW 2	NR	
117	STAFF OFFICE	CORRIDOR	3'-0"	7'-0"	WN2	HM1	HA	JA	HW 2	NR	
118	TECH OFFICE	CORRIDOR	3'-0"	7'-0"	WN2	HM1	HA	JA	HW 2	NR	
119	CORRIDOR	HALL	3'-0"	7'-0"	WNG	HM1	HA	JA	HW 1	45	
119A	HALL	CORRIDOR	4'-8"	7'-0"	CO	HM2	CB	CB	-	NR	
120	LAB	CORRIDOR	3'-0"	7'-0"	WN2	HM1	HA	JA	HW 2	NR	
121	TLT	CORRIDOR	3'-0"	7'-0"	WD	HM1	HA	JA	HW 5.1	NR	
122a	CORRIDOR	CORRIDOR	4'-0"	7'-0"	CO	HM2	CB	CB	-	NR	
124a	CORRIDOR	CORRIDOR	6'-0"	7'-0"	HFM	HM2	-	-	HW 3	NR	
124b	CORRIDOR	CORRIDOR	6'-0"	7'-0"	HFM	HM2	-	-	HW 3	NR	
201	CORRIDOR	RECEPTION	3'-0"	7'-0"	WD	HM1	CA	CA	HW 6	NR	
202	CORRIDOR	UNISEX FAMILY RESTROOM	3'-0"	7'-0"	WD	HM1	CA	CA	HW 5	NR	
203	CORRIDOR	JANITOR	3'-0"	7'-0"	WD	HM1	CA	CA	HW 7	NR	
204	WOMENS RESTROOM	CORRIDOR	3'-0"	7'-0"	WD	HM1	CA	CA	HW 9	NR	
207	CLASSROOM	ELEC / HVAC	3'-0"	7'-0"	WD	HM1	CA	CA	HW 8	NR	
208	CLASSROOM	STORAGE	3'-0"	7'-0"	WD	HM1	CA	CA	HW 8	NR	
247	CLASSROOM	HVAC	3'-0"	7'-0"	WD	HM1	CA	CA	HW 8	NR	
248	CORRIDOR	MENS RESTROOM	3'-0"	7'-0"	WD	HM1	CA	CA	HW 9	NR	


Hardware Set#:	1 (Office)	2 (Classroom)	3	4 (Storage Pair)	5 (TLT / Privacy Set)	6 (Office)	7 (Single Storage)	8 (Single Storage)	9 (Main Restrooms)	10
3 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	US28D	6 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	US28D	3 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	3 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	US28D
1 EA SAR Lockset	28-7005 x LL x MK Office	US28D	2 EA VON Exit Device	VON 98-27	US28D	1 EA SAR Lockset	28-7004 x LL x MK Classroom	1 EA SAR Lockset	28-7004 x LL x MK Classroom	US28D
1 EA SAR Door Closer	TB-281-O	EN	1 EA Removable mullion	1905 x B4E x 10" x 34"	US32D	2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	1 EA SAR Door Closer	TB-281-O	EN
2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	US32D	4 EA HHC Kick Plate	1905 x B4E x 10" x 34"	US32D	1 EA HHC Wall Bumper	236W	2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	US32D
1 EA HHC Wall Bumper	236W	US32D	2 EA SAR Door Closer	TB-281-O	EN	3 EA HHC Wall Bumper	236W	1 EA HHC Wall Bumper	236W	US32D
3 EA HHC Wall Bumper	236W	US32D	2 EA SAR Door Closer	TB-281-O	EN	1 EA HHC Silencer	307D	3 EA HHC Silencer	307D	Grey
1 EA SAR Door Closer	TB-281-O	EN	2 EA SAR Door Closer	TB-281-O	EN	1 EA SAR Door Closer	TB-281-O	1 EA SAR Door Closer	TB-281-O	EN
3 EA HHC Silencer	307D	Grey	2 EA HHC Hinge - Continuous	780-541HD x 83"DA	Clear	3 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	3 EA HHC Hinge	ECBB1100 4 1/2" x 4 1/2"	US28D
1 EA SAR Door Closer	TB-281-O	EN	2 EA HHC Flush-Bolt	282D	US28D	1 EA SAR Lockset	28-7004 x LL x MK Classroom	1 EA SAR Lockset	28-7004 x LL x MK Classroom	US28D
2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	US32D	1 EA SAR Door Closer	280X	US28D	1 EA SAR Door Closer	TB-281-O	1 EA SAR Door Closer	TB-281-O	EN
1 EA HHC Wall Bumper	236W	US32D	2 EA HHC Kick Plate	28-7004 x LL x MK Classroom	US28D/Active	2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	2 EA HHC Kick Plate	1905 x B4E x 10" x 40"	US32D
3 EA HHC Silencer	307D	Grey	2 EA HHC Kick Plate	6016 x Surface Mount x Slw 2	US32D	1 EA HHC Wall Bumper	236W	1 EA HHC Wall Bumper	236W	US32D
2 EA SAR Door Closer	TB-281-O	EN	2 EA HHC Silencer	307D	Grey	3 EA HHC Silencer	307D	3 EA HHC Silencer	307D	Grey
3 EA HHC Silencer	307D	Grey	3 EA HHC Silencer	TB-281-O	EN	3 EA HHC Silencer	307D	3 EA HHC Silencer	307D	Grey




1 | Head HA - HM Door Frame (Typ)
A2-2 | 3" = 1'-0"




2 | Jamb JA - HM Door Frame (Typ)
A2-2 | 3" = 1'-0"




3 | Head CA - HM Door Frame (Typ at CMU)
A2-2 | 3" = 1'-0"




4 | Jamb CA - HM Door Frame (Typ at CMU)
A2-2 | 3" = 1'-0"




7 | Jamb CA - HM Door Frame (Typ at CMU) W/ GWB
A2-2 | 3" = 1'-0"





8 | Jamb CA - HM Door Frame (Typ at CMU) W/ GWB both sides
A2-2 | 3" = 1'-0"




5 | Head HB - HM Cased Opng Frame
A2-2 | 3" = 1'-0"




6 | Jamb JB - HM Cased Opng Frame
A2-2 | 3" = 1'-0"




24 | FRAMES - HM Interior
A2-2 | 3" = 1'-0"



9 | Head CB - HM Cased Opng Frame (CMU)
A2-2 | 3" = 1'-0"



10 | Jamb CB - HM Cased Opng Frame (CMU)
A2-2 | 3" = 1'-0"



3 | Frame Elevations
3/8" = 1'-0"

Renovations of
**Baywood
Technology &
Community Center**



Address
Address




These drawings are the property of WM2 Architects. No part of these drawings may be reproduced or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of WM2 Architects.
Project Status: Working Drawings
Revision No. (if any):
Revision Date:
Project No.: 2021-003
Current Date: 10/25/21
Drawing Name:

Door Schedule and Details


A2-2




1 SLIDER WINDOW HEAD
A2-3 | 1 1/2" = 1'-0"




2 SLIDER WINDOW JAMB
A2-3 | 1 1/2" = 1'-0"




3 SLIDER WINDOW SILL
A2-3 | 1 1/2" = 1'-0"




6 Head CC - HM View Window Frame (Typ)
A2-3 | 3" = 1'-0"




7 Jamb CC - HM View Window Frame (CMU)
A2-3 | 3" = 1'-0"



1 SLIDING WINDOW




2 FIXED WINDOW




3 DRIVE-THRU WINDOW

8 WINDOW ELEVATIONS
A2-3 | 1" = 1'-0"



4 Demolition for New Drive Thru Pharmacy
A2-3 | 3/8" = 1'-0"



5 New Drive Thru Pharmacy Transaction Window
A2-3 | 3/8" = 1'-0"



GLAZING LEGEND	
GL-1	1/4" CLEAR TEMPERED FOR USE IN DOOR VIEW AND SIDE LITES OF UNRATED DOORS AND VIEW WINDOWS
GL-2	9/16" CLEAR LAMINATED TEMPERED FOR USE IN DOOR VIEW LITES OF 45 MIN RATED DOORS
GL-3	9/16" CLEAR LAMINATED TEMPERED FOR USE IN DOOR VIEW LITES OF 90 MIN RATED DOORS
IG-1	INSULATING GLASS W/ TEMPERED LITE AT INTERIOR AND EXTERIOR STOREFRONT WINDOWS
SP-1	INSULATED SPANDREL GLASS W/ TEMPERED LITE AT INTERIOR AND EXTERIOR STOREFRONT WINDOWS

REMOVE EXISTING GLAZING AND FRAME. RETROFIT NEW TRANSACTION WINDOW INTO EXISTING WINDOW SYSTEM.


NEW METAL CANOPY ATTACHED TO BUILDING. SEE CANOPY DETAILS SHEET.

NEW SLIDING DRIVE-THRU TRANSACTION WINDOW. QUIK-SERY BRDF1-48S1 THAT DOES NOT SLIDE WITH INTEGRATED SPEAKERS AS THE BASIS OF DESIGN. LOCATE BETWEEN EXISTING MULLIONS.






Window Schedule				
Type Mark	Height	Width	Description	Count
1	4'-0"	5'-0"	SLIDING/LOCKABLE TRANSACTION WINDOW	2
2	4'-0"	5'-0"	FIXED GLASS WINDOW	2
3	4'-3"	4'-0"	TRANSACTION WINDOW AND DRAWER COMBINATION UNIT	1



**ISOMETRIC VIEW
 OF CANOPY**



**SECTION VIEW
 OF CANOPY**




1.02 Design Criteria:
 A. International Building Code 2018
 B. ASCE 7-10
 C. Aluminum Design Manual 2019
 D. Local governing codes and standards for site location

1.03 Materials:
 A. All materials shall be extruded from aluminum unless indicated otherwise on the drawing.
 B. Material sizes shall meet or exceed the design criteria on 1.02

1.04 Finishes:
 A. Factory applied baked enamel to comply with AAMA 2603
 B. Color selected from manufacturers standard colors

1.05 Manufacturers:
 A. Mitchell Metals, LLC - www.mitchellmetals.net - 770-431-7300
 B. Diltmer - www.diltdeck.com - 407-699-1755




PARTITION TYPE LEGEND







WALL TYPES			SYMBOL DESIGNATION		WALL HATCH PATTERN LEGEND	
C	CMU (MAY HAVE FURRING)		FOR WALL TYPES INDICATED TO RECEIVE SOUND ATTENUATION, EXTEND SOUND ATTENUATION TO FULL HEIGHT OF WALL UNLESS OTHERWISE INDICATED. REFER TO INDIVIDUAL WALL TYPE MODIFIER FOR STC RATINGS.	NON-RATED METAL STUD PARTITION		
G	GYPSUM BOARD WITH METAL STUDS			NON-RATED SMOKE PARTITION		
S	SHAFT WALL			1 HOUR RATED FIRE BARRIER		
W	GYPSUM BOARD WITH WOOD STUDS			2 HOUR RATED FIRE BARRIER		
WALL TYPE			WALL TYPE MODIFIER		FIRE RATING OR PARTITION HEIGHT	
STUD/CMU WIDTH			WALL TYPE MODIFIER		FIRE RATING OR PARTITION HEIGHT	
WALL TYPE			WALL TYPE MODIFIER		FIRE RATING OR PARTITION HEIGHT	
STUD/CMU WIDTH			WALL TYPE MODIFIER		FIRE RATING OR PARTITION HEIGHT	

GENERAL NOTES - RATED ASSEMBLIES

- Protect and seal openings through floors, ceilings, and roofs to a one-hour or two-hour rating standard as indicated on the drawings. Seal all penetrations through rated walls and floors with a material capable of preventing the passage of flames and hot gases and to meet test standards for fire stopping (ASTM E 814 or NFPA 251).
- Permanently identify all fire walls with a sign with 2-inch high lettering on a contrasting background. Place signs 12-feet apart, maximum, and locate above ceiling. (At spaces with no ceiling, located within 18-inches of underside of floor above.) Provide one sign, minimum, per wall or barrier. Provide the following text:
 - "1-HOUR FIRE RATED WALL - PROTECT ALL OPENINGS"
 - "2-HOUR FIRE RATED WALL - PROTECT ALL OPENINGS"
- Permanently identify all smoke barrier walls with a sign with 2-inch high lettering on a contrasting background. Place signs 12-feet apart, maximum, and locate above ceiling. (At spaces with no ceiling, located within 18-inches of underside of floor above.) Provide one sign, minimum, per wall or barrier. Provide the following text:
 - "1-HOUR SMOKE BARRIER WALL - PROTECT ALL OPENINGS"
 - "2-HOUR SMOKE BARRIER WALL - PROTECT ALL OPENINGS"



B FULL-HGT PARTITION 1 1/2" = 1'-0"
C RATED WALL 1 1/2" = 1'-0"
E FURRING PARTITION 1 1/2" = 1'-0"



3 Rated Partition - Horizontal Joint Layout A4-1A 1 1/2" = 1'-0"






4 Rated Partition - Vertical Joint Layout A4-1A 1 1/2" = 1'-0"

5 Rated Partition - Hierarchy Diagram A4-1A 1 1/2" = 1'-0"

6 Partition Backing Support A4-1A 1 1/2" = 1'-0"

7 Attachment at Grab Bars A4-1A 3" = 1'-0"

8 Bulkhead at Casework A4-1A 1 1/2" = 1'-0"








9 Rated Partition Perpendicular to Metal Deck A4-1A 1 1/2" = 1'-0"

10 Rated Partition Parallel to Metal Deck A4-1A 1 1/2" = 1'-0"

11 Rated Partition Perpendicular to Beam A4-1A 1 1/2" = 1'-0"

12 Rated Partition under Beam A4-1A 1 1/2" = 1'-0"

13 Rated Partition 10\"/>



14 Rated Partition Adjacent to Beam A4-1A 1 1/2" = 1'-0"

15 Multiple Conduit Penetrations at Rated Partition A4-1A 1 1/2" = 1'-0"

16 Single Conduit or Pipe Penetration at Rated Partition A4-1A 1 1/2" = 1'-0"

17 Duct Penetration at Rated Partition A4-1A 1 1/2" = 1'-0"

18 Stud Framing at Doors/Windows A4-1A 1 1/2" = 1'-0"

19 Recessed Cabinet in Non-rated or One Hour Partition A4-1A 1 1/2" = 1'-0"

20 Recessed Cabinet in Two Hour Partition A4-1A 1 1/2" = 1'-0"

21 Semi-recessed Cabinet in Non-rated or One Hour Partition A4-1A 1 1/2" = 1'-0"



Renovations of
Baywood Technology & Community Center
 Address
 Address

B.E.C.I.
 SOLUTIONS BY DESIGN

Beekman Point
 ENGINEERING

These drawings contain certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WMA Architects/Engineers, Inc. (WMA) and WMA Architects/Engineers, Inc. (WMA) are the authors of these drawings. All rights reserved. Unpublished and/or confidential information is forbidden.

Project Status: **Working Drawings**

Revision No. (if any): **2021-003** Revision Date: **10/25/21**

Project No.: **2021-003** Current Date: **10/25/21**


Drawing Name: **A4-1A**

Wall Types and Details - Metal Framing

A4-1A

PARTITION TYPE LEGEND






WALL TYPES			WALL TYPE DESIGNATION		WALL HATCH PATTERN LEGEND	
C	CMU (MAY HAVE FURRING)		STUD/CMU WIDTH	FOR WALL TYPES INDICATED TO RECEIVE SOUND ATTENUATION, EXTEND SOUND ATTENUATION TO FULL HEIGHT OF WALL UNLESS OTHERWISE INDICATED. REFER TO INDIVIDUAL WALL TYPE MODIFIER FOR STC RATINGS.	NON-RATED METAL STUD PARTITION	
G	GYPSUM BOARD WITH METAL STUDS		WALL TYPE MODIFIER		NON-RATED SMOKE PARTITION	
S	SHAFT WALL		FIRE RATING OR PARTITION HEIGHT		1 HOUR RATED FIRE PARTITION	
W	GYPSUM BOARD WITH WOOD STUDS				2 HOUR RATED FIRE BARRIER	
					1 HOUR RATED FIRE/SMOKE BARRIER	
					2 HOUR RATED FIRE/SMOKE BARRIER	
					NON RATED MASONRY	
					1 HOUR RATED MASONRY FIRE BARRIER (UL# U90S)	
					2 HOUR RATED MASONRY FIRE BARRIER (UL# U90S)	



WHERE WALL IS INDICATED TO BE 1-HOUR RATED, PROVIDE CONCRETE MASONRY UNITS CAPABLE OF SUCH RATING PER TABLE 721.3.2.2 OF THE INTERNATIONAL BUILDING CODE. SUBMIT WRITTEN EVIDENCE OF SAME FOR REVIEW BY ARCHITECT PRIOR TO USE OF SUCH MASONRY UNITS.

GENERAL NOTES - RATED ASSEMBLIES

- Protect and seal openings through floors, ceilings, and roofs to a one-hour or two-hour rating standard as indicated on the drawings. Seal all penetrations through rated walls and floors with a material capable of preventing the passage of flames and hot gases and to meet test standards for fire stopping (ASTM E 814 or NFPA 251).
- Permanently identify all fire walls with a sign with 2-inch high lettering on a contrasting background. Place signs 12-feet apart, maximum, and locate above ceiling. (At spaces with no ceiling, located within 18-inches of underside of floor above.) Provide one sign, minimum, per wall or barrier. Provide the following text:
 1-HOUR FIRE RATED WALL - PROTECT ALL OPENINGS
 2-HOUR FIRE RATED WALL - PROTECT ALL OPENINGS
- Permanently identify all smoke barrier walls with a sign with 2-inch high lettering on a contrasting background. Place signs 12-feet apart, maximum, and locate above ceiling. (At spaces with no ceiling, located within 18-inches of underside of floor above.) Provide one sign, minimum, per wall or barrier. Provide the following text:
 1-HOUR SMOKE BARRIER WALL - PROTECT ALL OPENINGS
 2-HOUR SMOKE BARRIER WALL - PROTECT ALL OPENINGS



Renovations of
**Baywood
Technology &
Community Center**
Address
Address



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
 © 2021, WM2A Architects/Planners, Inc.
 (5/13) WM2A Architects
 These drawings, as instruments of service, remain the property of the architect. Unauthorized use or reproduction is forbidden.
 Project Status: Working Drawings
 Revision No (if any): Revision Date:
 Project No: 2021-003 Current Date: 10/25/21
 Drawing Name: Wall Types and Details - Masonry


- Ceiling Ac1
24" x 24"
Acoustical Ceiling Tile
15/16" grid
- Ceiling Gb1
Gypsum Board Ceiling
- Open to structure above
Paint structure P-2
- DIFFUSER - SQUARE SUPPLY
- REGISTER - SQUARE RETURN
- REGISTER - EXHAUST
- LIGHTING - RECESSED FIXTURE
- LIGHTING - RECESSED FIXTURE
- LIGHTING - RECESSED DOWN LIGHT
- EXIT SIGN
- SPEAKER
- LIGHTING - PENDANT FIXTURE 6" MOUNT
- SUSPENDED LINEAR FIXTURE

Note:
Reflected ceiling plan(s) on architectural drawings often do NOT indicate all ceiling-mounted items. See drawings of other disciplines for additional items. Coordinate installation of all required ceiling items.

Color shades used on reflected ceiling plans and legends are provided to help the Contractor identify types of ceilings. These shades do NOT indicate finish colors.

LEGEND - REFLECTED CEILING PLAN

1/8" = 1'-0"



2 TYPICAL CEILING BULKHEAD

A6-1 3/4" = 1'-0"

KEYNOTES - NEW WORK - FLOOR PLANS	
NO.	DESCRIPTION
1	ALIGN NEW WALL WITH EXISTING
2	INFILL WALL TO MATCH EXISTING CONSTRUCTION.
3	PROVIDE SOUND SEALS FOR DOOR.
4	REMOTE WATER SHUT OFF
5	PROVIDE WINDOW SPEAKER
6	INSTALL NEW PLUMBING FIXTURES
7	INSTALL NEW CASEWORK
8	PROVIDE 4X8 SHEET OF DEDICATED PLYWOOD FOR MOUNTING DATA EQUIPMENT
9	PREPARE ROOM FOR NEW FINISHES, AND INSTALL NEW FINISHES AS SCHEDULED.
10	INSTALL EQUIPMENT AND ACCESSORIES
11	PROVIDE NEW DOOR SIGNAGE
12	INSTALL NEW PASS THROUGH CABINET.
13	INSTALL NEW COOKSON (TM) MOTOR OPERATED, BRICK PATTERN, ROLLING GRILLE, WALL MOUNTED SECURITY GATE ABOVE CEILING AT PHARMACY WINDOW. SECURITY GATE TO COVER THE ENTIRE GLAZING SYSTEM. SEE MANUFACTURER SPECIFICATIONS FOR MOUNTING INSTRUCTIONS AND CEILING SPACING REQUIREMENTS
14	INSTALL NEW ADA HI-LO DRINKING FOUNTAIN
15	INSTALL NEW TOPPING COAT, AND INSTALL NEW LVT


KEYNOTES - NEW WORK - CEILINGS	
NO.	DESCRIPTION
1	INSTALL NEW ACOUSTICAL CEILING TILE ACCORDING TO PLANS
2	INSTALL NEW LIGHT FIXTURES ACCORDING TO PLAN
3	ALL CEILINGS TO COORDINATE WITH MEP PLANS



1 First Floor Plan - Phase 1

A6-1 3/16" = 1'-0"

SCALE: 3/16" = 1'-0"




Address
Address

TOILET ACCESSORIES BY ROOM PHASE 1


ROOM NO.	ROOM NAME	TYPE MARK	DESCRIPTION	COUNT	O.C./C.C./O.O.
103	TRIAGE	T6	Hand Sanitizer Dispenser	1	O.C.
103	TRIAGE	T7	Soap Dispenser	1	O.C.
103	TRIAGE	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
104	EXAM 1	T6	Hand Sanitizer Dispenser	1	O.C.
104	EXAM 1	T7	Soap Dispenser	1	O.C.
104	EXAM 1	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
105	EXAM 2	T6	Hand Sanitizer Dispenser	1	O.C.
105	EXAM 2	T7	Soap Dispenser	1	O.C.
105	EXAM 2	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
106	EXAM 3	T6	Hand Sanitizer Dispenser	1	O.C.
106	EXAM 3	T7	Soap Dispenser	1	O.C.
106	EXAM 3	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
107	TELEMED EXAM	T6	Hand Sanitizer Dispenser	1	O.C.
107	TELEMED EXAM	T7	Soap Dispenser	1	O.C.
107	TELEMED EXAM	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
111	STAFF TLT	T1	18" Grab Bar (Vertical)	1	C.C.
111	STAFF TLT	T3	36" Grab Bar	1	C.C.
111	STAFF TLT	T4	42" Grab Bar	1	C.C.
111	STAFF TLT	T6	Hand Sanitizer Dispenser	1	O.C.
111	STAFF TLT	T7	Soap Dispenser	1	O.C.
111	STAFF TLT	T8	ADA Surface Mounted Automatic Hand Dryer	1	O.C.
111	STAFF TLT	T10	Toilet Paper Dispenser	1	O.C.
111	STAFF TLT	T14	18" x 36" Mirror	1	C.C.
111	STAFF TLT	T17	Surface Mounted Sanitary Napkin Disposal	1	O.C.
114	PHARMACY	T6	Hand Sanitizer Dispenser	1	O.C.
114	PHARMACY	T7	Soap Dispenser	1	O.C.
114	PHARMACY	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
115	BREAKROOM	T6	Hand Sanitizer Dispenser	1	O.C.
115	BREAKROOM	T7	Soap Dispenser	1	O.C.
115	BREAKROOM	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
120	LAB	T6	Hand Sanitizer Dispenser	1	O.C.
120	LAB	T7	Soap Dispenser	1	O.C.
120	LAB	T8	ADA Surface Mounted Automatic Hand Dryer	1	O.C.
120	LAB	T30	Specimen Pass-Thru Cabinet	1	C.C.
120A	LAB	T6	Hand Sanitizer Dispenser	1	O.C.
120A	LAB	T7	Soap Dispenser	1	O.C.
120A	LAB	T9	Paper Towel Dispenser, surface-mounted.	1	O.C.
121	TLT	T1	18" Grab Bar (Vertical)	1	C.C.
121	TLT	T3	36" Grab Bar	1	C.C.
121	TLT	T4	42" Grab Bar	1	C.C.
121	TLT	T6	Hand Sanitizer Dispenser	1	O.C.
121	TLT	T7	Soap Dispenser	1	O.C.
121	TLT	T8	ADA Surface Mounted Automatic Hand Dryer	1	O.C.
121	TLT	T10	Toilet Paper Dispenser	1	O.C.
121	TLT	T14	18" x 36" Mirror	1	C.C.
121	TLT	T17	Surface Mounted Sanitary Napkin Disposal	1	O.C.
202	UNISEX FAMILY RESTROOM	T1	18" Grab Bar (Vertical)	1	C.C.
202	UNISEX FAMILY RESTROOM	T3	36" Grab Bar	1	C.C.
202	UNISEX FAMILY RESTROOM	T4	42" Grab Bar	1	C.C.
202	UNISEX FAMILY RESTROOM	T6	Hand Sanitizer Dispenser	1	O.C.
202	UNISEX FAMILY RESTROOM	T7	Soap Dispenser	1	O.C.
202	UNISEX FAMILY RESTROOM	T8	ADA Surface Mounted Automatic Hand Dryer	4	O.C.
202	UNISEX FAMILY RESTROOM	T10	Toilet Paper Dispenser	1	O.C.
202	UNISEX FAMILY RESTROOM	T15	24" x 36" Mirror	1	C.C.
202	UNISEX FAMILY RESTROOM	T17	Surface Mounted Sanitary Napkin Disposal	1	O.C.
250	WOMENS RESTROOM	T1	18" Grab Bar (Vertical)	1	C.C.
250	WOMENS RESTROOM	T3	36" Grab Bar	1	C.C.
250	WOMENS RESTROOM	T4	42" Grab Bar	1	C.C.
250	WOMENS RESTROOM	T6	Hand Sanitizer Dispenser	2	O.C.
250	WOMENS RESTROOM	T7	Soap Dispenser	2	O.C.
250	WOMENS RESTROOM	T8	ADA Surface Mounted Automatic Hand Dryer	2	O.C.
250	WOMENS RESTROOM	T10	Toilet Paper Dispenser	3	O.C.
250	WOMENS RESTROOM	T14	18" x 36" Mirror	3	C.C.
250	WOMENS RESTROOM	T17	Surface Mounted Sanitary Napkin Disposal	3	O.C.
251	MENS RESTROOM	T1	18" Grab Bar (Vertical)	1	C.C.
251	MENS RESTROOM	T3	36" Grab Bar	1	C.C.
251	MENS RESTROOM	T4	42" Grab Bar	1	C.C.
251	MENS RESTROOM	T6	Hand Sanitizer Dispenser	2	O.C.
251	MENS RESTROOM	T7	Soap Dispenser	2	O.C.
251	MENS RESTROOM	T8	ADA Surface Mounted Automatic Hand Dryer	2	O.C.
251	MENS RESTROOM	T10	Toilet Paper Dispenser	1	O.C.
251	MENS RESTROOM	T14	18" x 36" Mirror	3	C.C.

TOILET ACCESSORY SCHEDULE


Type Mark	Count	Item	Image	Description	Model
T1	5	18" Grab Bar (Vertical)		1 1/4" diameter, heavy-duty satin-finish stainless steel, concealed mounting.	ASI 3700 series, Bobrick B-5806, Bradley 832.
T3	5	36" Grab Bar		1 1/4" diameter, heavy-duty satin-finish stainless steel, concealed mounting.	ASI 3700 series, Bobrick B-5806, Bradley 832.
T4	5	42" Grab Bar		1 1/4" diameter, heavy-duty satin-finish stainless steel, concealed mounting.	ASI 3700 series, Bobrick B-5806, Bradley 832.
T6	16	Hand Sanitizer Dispenser		Surface-mtd, vertical, satin-finish stainless steel, manual dispenser.	Select dispenser for product being dispensed.
T7	16	Soap Dispenser		Surface-mtd, vertical, satin-finish stainless steel, 40 oz capacity.	ASI 0347, Bobrick B-2111, Bradley 6562
T8	11	ADA Surface Mounted Automatic Hand Dryer		Satin-finish, stainless steel, ADA Surface Mounted Automatic Hand Dryer	Bobrick B-7128 208-240V, ASI 0185-93, Bradley 2902-287400
T9	8	Paper Towel Dispenser		Satin-finish stainless steel, dispenses 400 C-fold or S2S multi-fold, surface mounting.	ASI 0210, Bobrick B-262, Bradley 250-15.
T10	7	Toilet Paper Dispenser		Dual-roll dispenser, cast aluminum, non-controlled delivery.	ASI 0264-1A, Bobrick B-2740, Bradley 5243-50.
T14	8	18" x 36" Mirror		Mirror with channel frame.	ASI 0620 series, Bobrick B-165, Bradley 781.
T15	1	24" x 36" Mirror		Mirror with channel frame.	ASI 0620 series, Bobrick B-165, Bradley 781.
T17	6	Surface Mounted Sanitary Napkin Disposal		Satin-finish stainless steel, 1.2 gallon plastic liner, lockable.	ASI 0473-1A, Bobrick B-254, Bradley 4722-15.
T30	1	Specimen Pass-Thru Cabinet		Type 304 stainless steel, satin finish. Self-closing doors. Interlocking mechanism prevents both doors from being open at the same time; provides sight barrier. Removable stainless steel tray.	ASI 8154, Bobrick B-505, Bradley 9813.




1 | First Floor Plan - Equipment Plan - Phase 1
A7-2 | 3/16" = 1'-0"












2 | Phase 1.1 Patient Toilet Callout
A7-2 | 1/2" = 1'-0"



3 | Phase 1.1 Staff Toilet Callout
A7-2 | 1/2" = 1'-0"



4 | Patient Toilet Elevation - Passthru Location
A7-2 | 3/8" = 1'-0"





LEGEND - ADA ACCESSIBLE FIXTURES
3/8" = 1'-0"

SPECIALTY EQUIPMENT SCHEDULE

CATEGORY	TYPE MARK	DESCRIPTION	COUNT	O.C./C.C./O.O.
FURNITURE	F6	GUEST CHAIRS	16	O.O.
GENERAL EQUIPMENT	E200	MICROWAVE, ABOVE RANGE	1	O.C.
GENERAL EQUIPMENT	E201	DUAL COOKTOP	1	C.C.
GENERAL EQUIPMENT	E202	COFFEE POT	1	C.C.
GENERAL EQUIPMENT	E203	Refrigerator, Domestic, w/Freezer, Side-by-Side	1	O.C.
GENERAL EQUIPMENT	E205	PRINTER / COPIER / FAX	1	O.C.
GENERAL EQUIPMENT	G107	SECURITY GATE AT PHARMACY WINDOW	1	C.C.
GENERAL EQUIPMENT	TV02	42" FLAT SCREEN TV	1	O.C.
MEDICAL EQUIPMENT	M101	LAB REFRIGERATOR	2	O.C.
MEDICAL EQUIPMENT	M102	LAB HALF SIZE REFRIGERATOR	1	O.C.
MEDICAL EQUIPMENT	M103	OTOSCOPE	4	O.C.
MEDICAL EQUIPMENT	M104	FLOOR SCALE	1	O.O.

FIXTURE AND ACCESSORY MOUNTINGS NOTES:
 1. Install accessories at mounting heights indicated UNDO.
 2. Provide partition blocking for wall-mounted items, such as grab bars. (See Partition Blocking detail.)
 3. Provide indicated clear floor space for all fixtures and accessories.
 4. Where accessories are indicated to be installed on or within toilet partitions, coordinate required fastening reinforcements, cutouts, and other required accommodations with the fabrication and installation of the toilet partition system.
 5. Provide/Install flush valve controls that are accessible from interior of room UNDO.







1 FIRST FLOOR PHASE 1 OVERALL MECHANICAL PLAN
 M1-01 3/16" = 1'-0"



ARCHITECTS
WM2A.COM
403B NORTH MAIN ST
HILLSVILLE, VA 24343



Renovations of
Baywood
Technology &
Community Center
247 Grammar Lane,
Galax, VA 24333


1 ROOF MECHANICAL PLAN
M1-02 1/8" = 1'-0"




These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
© 2021, WM2A Architects/Planners, Inc. All Rights Reserved.
These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.
Project Status:
ISSUE FOR CONSTRUCTION
Revision No (if any): 0 Revision Date: 10/25/2021
Project No: 21006-3 Current Date: 10/25/2021
Drawing Name:

ROOF MECHANICAL PLAN
Drawing No: M1-02

KEYNOTES
 1 ROUTE 4" EIA DUCT THROUGH WALL AND FINISH WITH ALUMINUM WALL CAP SIMILAR TO GREENHECK WC-4



1 FIRST FLOOR PHASE 1 ENLARGED MEDICAL AREA MECHANICAL PLAN
 M2-01 1/4" = 1'-0"



2 FIRST FLOOR PHASE 1 ENLARGED MEDICAL AREA MECHANICAL PLAN
 M2-01 1/4" = 1'-0"


Renovations of
 Baywood
 Technology &
 Community Center
 247 Grammar Lane,
 Galax, VA 24333




These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
 © 2021, WMA Architects/Planners, Inc. All Rights Reserved.
 These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.
 Project Status:
 ISSUE FOR CONSTRUCTION
 Revision No. (if any): 0 Revision Date: 10/25/2021
 Project No.: 210063 Current Date: 10/25/2021
 Drawing Name:
 FIRST FLOOR PHASE 1 ENLARGED MECHANICAL PLAN
 Drawing No.: M2-01



ARCHITECTS
WM2A.COM
403B NORTH MAIN ST
HILLSVILLE, VA 24343



Renovations of
Baywood
Technology &
Community Center
247 Grammar Lane,
Galax, VA 24333



1 FIRST FLOOR PHASE 1 ENLARGED CLASSROOM AREA MECHANICAL PLAN
M2-02 1/4" = 1'-0"




These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
© 2021, WM2A Architects/Planners, Inc.
All rights reserved. These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status:
ISSUE FOR CONSTRUCTION
Revision No. (if any): 0 Revision Date: 10/25/2021
Project No.: 21006-3 Current Date: 10/25/2021


Drawing Name:
FIRST FLOOR PHASE 1
ENLARGED MECHANICAL
PLAN

Drawing No.:
M2-02




- NOTES:
1. PACK ROOF CURB WITH FIBERGLASS INSULATION FOR ACOUSTICAL BENEFITS.
 2. CONDENSATE TO DRAIN TO NEAREST ROOF DRAIN.
 3. FOLLOW ALL MANUFACTURER'S INSTALLATION RECOMMENDATIONS.

1 DOWNFLOW RTU DETAIL
M5-01 NOT TO SCALE




- NOTES:
1. SEE FLOOR PLANS FOR DUCT SIZES.
 2. INSULATION MINIMUM 4" CLEAR ON ALL SIDES AS DUCT PASSES THROUGH JOIST
 3. IF ASPECT RATIO MUST BE CHANGED TO MAINTAIN CLEARANCE, AREA OF INSIDE DUCT SHALL REMAIN THE SAME OR LARGER AS SHOWN ON THE FLOOR PLANS.

7 DUCT THROUGH TRUSS DETAIL
M5-01 NOT TO SCALE




10 LOW VELOCITY DUCTWORK BRANCH TAKEOFF DETAIL
M5-01 NOT TO SCALE




- NOTES:
1. SET AHU ON PRESSURE TREATED 2"x4" RUNNERS (LENGTH OF AHU IN THE DRAIN PAN).
 2. PROVIDE A FLOAT SWITCH TO SHUT DOWN UNIT IF SECONDARY DRAIN PAN FILLS WITH WATER.
 3. FILTER SHALL BE REMOVABLE WITHOUT TOOLS.
 4. FIELD ROUTE CONDENSATE DRAIN TO OUTSIDE OF BUILDING. SEE CONDENSATE DRAIN FIELD DETAIL.
 5. PROVIDE 24 VOLT MOTORIZED, LOW LEAK DAMPER ACTUATOR (RUSKING MODEL CDRS2S) AND INTERLOCK WITH COMPRESSOR. THE NORMALLY CLOSED DAMPER SHALL ONLY OPEN WHEN COMPRESSOR IS OPERATING IN HEATING OR COOLING MODE.

2 HORIZONTAL AHU DETAIL
M5-01 NOT TO SCALE




- NOTE:
- SINGLE THICKNESS TYPE TURNING VANES RADIUS AND SPACING SHALL BE PROVIDED PER THIS DETAIL.


8 SINGLE THICKNESS VANE ELBOW DETAIL
M5-01 NOT TO SCALE




STANDARD RECTANGULAR BRANCH TAKE-OFF
(BRANCH FLOW GREATER THAN 25% OF MAIN FLOW)




STANDARD RECTANGULAR DUCT BRANCH TAKE-OFF
(BRANCH FLOW LESS THAN 25% OF MAIN FLOW)



3 VAV (ELECRTC HEAT) DETAIL
M5-01 NOT TO SCALE




9 DUCT SPLITTER DETAIL
M5-01 NOT TO SCALE



ANGLE IRON AND FASTENER DIMENSIONS		
LENGTH	ANGLE SIZE (MIN)	FASTENER LOCATION
0-48"	1-1/2" X 1-1/2" X 1/8"	8" ON CENTER
49-96"	2" X 2" X 1/8"	6" ON CENTER
96" & OVER	2-1/2" X 2-1/2" X 3/16"	6" ON CENTER


- NOTES:
1. WHERE MANUFACTURER'S INSTRUCTIONS EXCEED THE REQUIREMENTS OF THIS DETAIL, THE MANUFACTURER'S INSTRUCTIONS SHALL BE FOLLOWED.

11 FIRE DAMPER DETAIL
M5-01 NOT TO SCALE




- NOTES:
1. ANCHOR TO BE 5/16" DIA CARBON STEEL ITW BULDEX TAPCON, EMBED 2 1/4" INTO CONCRETE AND SPACE 3 3/4" MINIMUM AWAY FROM ADJACENT ANCHOR.

4 ANCHOR TIE DOWN DETAIL
M5-01 NOT TO SCALE



- NOTES:
1. UTILIZE (2) STEEL CLIPS AT EACH CORNER FOR A TOTAL OF (8) PER UNIT.

5 HEAT PUMP PAD DETAIL
M5-01 NOT TO SCALE



6 TIE DOWN DETAIL
M5-01 NOT TO SCALE

ROOFTOP UNIT SCHEDULE																																																	
MARK	MANUFACTURER	MODEL NO.	TYPE	ARRANGEMENT	SUPPLY AIRFLOW			OUTSIDE AIR			PRESS			FAN			INCLUDE POWER EXHAUST			NOMINAL CAP			COOLING COIL			HEATING ELEMENT			COMPRESSOR			FILTER			DISCONNECT			NOTES											
					3,600 CFM	450 CFM	DCV	ESP	DRIVE TYPE	MOTOR	QTY	POWER	ECM	NO	10.0ton	TOTAL	SENSIBLE	EAT(DB)	EAT(MB)	LAT(DB)	LAT(MB)	NO	113.7/10 Bluh	70.0 °F	99.3 °F	Electric Resistance	QTY	POWER	SCR	STAGES	VOLT	PH	FLA	TYPE	CHARGE	LOW AMBIENT KIT	SUMMER AMBIENT DBT		WINTER AMBIENT DBT	SEER	EER	EFF	SEACOAST PROT	UNIT WEIGHT	MCA	MOCP	VOLT	PH	FURNISH BY
RTU1	TRANE	WH1C20	HEAT PUMP	DOWNFLOW	3,600 CFM	450 CFM	DCV	ESP	DRIVE TYPE	MOTOR	QTY	POWER	ECM	NO	10.0ton	121.9/0 Bluh	90.6/20 Bluh	80.0 °F	67.0 °F	55.0 °F	54.0 °F	Yes	113.7/10 Bluh	70.0 °F	99.3 °F	Electric Resistance	1	18 kW	Yes	3	208 V	3	50.0 A	R-410A	24 lb	No	95.0 °F	47.0 °F	15.5	11.5	30%	No	1617 lb	95.0 A	100.0 A	208 V	3	DIV. 26	1,2,3,4,5

- NOTES:
- PROVIDE MODEL SELECTED OR EQUIVALENT BY CARRIER.
 - PROVIDE WITH A LOCAL DISCONNECT, ENTHALPY ECONOMIZER, CONVENIENCE OUTLET, AND SINGLE POINT POWER CONNECTION.
 - PROVIDE UNIT WITH BAROMETRIC BUILDING PRESSURE RELIEF.
 - PROVIDE WITH SEACOAST COIL EPOXY COATING AND VIBRATION AND SEISMIC ISOLATION ROOF CURB.
 - PROVIDE AS MULTI-ZONE VAV CONFIGURED UNIT.

MZVAV AHU SEQUENCE OF OPERATIONS

GENERAL: UNIT IS A MULTI-ZONE VAV PACKAGED ROOFTOP UNIT WITH AN OUTSIDE AIR DAMPER, REFERENCE ENTHALPY ECONOMIZER WITH LOW LEAKAGE DAMPER, VARIABLE SPEED SUPPLY FAN, ELECTRIC RESISTANCE HEAT, RETURN AIR HUMIDITY SENSOR, SUPPLY AIR TEMPERATURE SENSOR, OUTSIDE AIR TEMPERATURE SENSOR, HOT GAS REHEAT, AND A BUILDING PRESSURE RELIEF FAN. UNIT SHALL BE FACTORY EQUIPPED WITH A BACNET CONTROLS PACKAGE AND A RETURN AIR SMOKE DETECTOR. RTU BACNET CONTROLLER SHALL BE OF THE SAME MANUFACTURER AS THE VAV CONTROLLERS VAV BOXES.

REMOTE OPERATORS INCLUDE: DUCT PRESSURE SENSOR, BUILDING PRESSURE SENSOR, LOCATED IN THE RETURN AIR DUCT (SEE PLANS), OUTDOOR BUILDING PRESSURE SENSOR LOCATED AT RTU (NOT SHOWN), RETURN AIR SMOKE DETECTOR WITH THE IN TO THE FIRE ALARM CONTROL PANEL (FACP) (BY FIRE ALARM CONTRACTOR), RETURN AIR CO2 CONCENTRATION SENSOR, AND DASY-CHAINED VAV CONTROLLERS.

OPERATION:

THE UNIT SHALL RUN CONTINUOUSLY.

THE RTU CONTROLLER SHALL POLL THE VAV CONTROLLERS AT A MAXIMUM OF 3 MINUTE INTERVALS FOR ZONE SETPOINT AND ZONE TEMPERATURE.

MODE OF OPERATION:

THE RTU CONTROLLER SHALL POLL THE VAV CONTROLLERS TO DETERMINE MODE (COOLING/HEATING) OF OPERATION. THE RTU MODE OF OPERATION SHALL BE BASED ON THE MAJORITY OF BOXES REQUESTED MODE.

SUPPLY FAN CONTROLS/OPTIMIZATION:

THE AHU CONTROLLER SHALL MONITOR REMOTE DUCT PRESSURE AND CONTROL SUPPLY FAN SPEED TO MAINTAIN AN INITIAL 1.5" WG (ADJ.) CONSTANT DUCT PRESSURE. FINAL REMOTE DUCT PRESSURE SHALL BE SET BY TEST AND BALANCE.

OUTSIDE AIR:

- THE CONTROLLER SHALL MEASURE THE RETURN AIR CO2 CONCENTRATION.
- IF RETURN AIR CONCENTRATION RISES TO 1000 PPM (ADJ.) THE RTU CONTROLLER SHALL OPEN THE OUTSIDE AIR DAMPER.
- UPON RETURN AIR CO2 CONCENTRATION LOWERING TO 500 PPM (ADJ.) THE CONTROLLER SHALL CLOSE THE OUTSIDE DAMPER.

COOLING MODE:

- COOLING SHALL BE ENABLED WHEN OUTSIDE AIR TEMPERATURE IS 60°F (ADJ.) OR GREATER. THE CONTROLLER SHALL STAGE THE COOLING OPERATION TO DELIVER 55 °F (ADJ.) SUPPLY AIR.

ECONOMIZER MODE:

- THE ECONOMIZER SHALL BE ENABLED WHENEVER OUTSIDE AIR TEMPERATURE IS LESS THAN 60°F (ADJ.). OUTSIDE AIR ENTHALPY IS 22 BTU/LB OR LESS, AND COOLING MODE IS ACTIVE. THE ECONOMIZER SHALL BE DISENGAGED WHENEVER OUTSIDE AIR TEMPERATURE DROPS TO 45°F TO °F (ADJ.) OR HEATING MODE IS ENGAGED.
- THE CONTROLLER SHALL MEASURE THE OUTSIDE AIR TEMPERATURE AND MODULATE THE ECONOMIZER DAMPER TO MAINTAIN 55°F (ADJ.) SUPPLY AIR TEMPERATURE. THE RTU CONTROLLER SHALL MAINTAIN MINIMUM OR GREATER OUTSIDE AIR PER THE SCHEDULE.

HEATING MODE:

- WHENEVER OUTSIDE AIR TEMPERATURE FALLS BELOW 55°F (ADJ.) HEATING MODE SHALL BE ENABLED WHENEVER OUTSIDE AIR TEMPERATURE FALLS BELOW 55°F (ADJ.).
- >35°F OUTSIDE AIR TEMPERATURE - THE CONTROLLER SHALL USE HEAT PUMP MODE AND LOCK OUT ELECTRIC HEATING.
- <35°F OUTSIDE AIR TEMPERATURE - THE CONTROLLER SHALL STAGE THE ELECTRIC HEATING TO PROVIDE 70°F (ADJ.) SUPPLY AIR TEMPERATURE.

DEHUMIDIFICATION MODE:

- THE CONTROLLER SHALL MEASURE THE RETURN AIR HUMIDITY AND OVERRIDE THE COOLING FUNCTION TO MAINTAIN RETURN AIR HUMIDITY AT OR BELOW 50% RH (ADJ.).
- DURING DEHUMIDIFICATION, THE CONTROLLER SHALL MODULATE HOT GAS REHEAT TO MAINTAIN SUPPLY AIR AT THE SUPPLY AIR TEMPERATURE COOLING SETPOINT.
- UPON RETURN AIR REDUCING TO 40% (ADJ.) RH OR LOWER, THE CONTROLLER SHALL RESTORE THE NORMAL MODE OF OPERATION.

BUILDING PRESSURE RELIEF:

- THE CONTROLLER SHALL MEASURE THE BUILDING PRESSURE.
- IF BUILDING PRESSURE SHOULD RISE TO 0.5" WC (ADJ.), THE RTU CONTROLLER SHALL ENGAGE THE BUILDING RELIEF FAN UNTIL BUILDING PRESSURE LOWERS TO 0.2" WC (ADJ.) THEN DISENGAGE THE BUILDING PRESSURE RELIEF SYSTEM.

STARTUP SEQUENCE: UPON SIGNAL OR COMMAND TO STARTUP, THE RTU CONTROLLER SHALL:

- OPEN THE OUTSIDE AIR DAMPER
- UPON PROOF OF OUTSIDE AIR DAMPERS OPEN, START THE SUPPLY FANS.

SHUTDOWN/STANDBY SEQUENCE: UPON A SIGNAL OR COMMAND TO SHUTDOWN, THE RTU CONTROLLER SHALL:

- STOP THE SUPPLY FANS
- UPON PROOF OF SUPPLY FAN OFF, CLOSE THE OUTSIDE AIR DAMPERS

EMERGENCY AND OVERRIDE MODES:

- SMOKE DETECTION
- UPON RECEIPT OF A SMOKE DETECTOR ALARM THE CONTROLLER SHALL INITIATE THE SHUTDOWN SEQUENCE AND SIGNAL THE FACP TO PROVIDE AN ALARM. A MANUAL RESET SHALL BE REQUIRED PRIOR TO OPERATION FOLLOWING A SMOKE DETECTOR SHUTDOWN.
- FACP ALARM
- FIRE ALARM ACTUATION: THE CONTROLLER SHALL ACCEPT A REMOTE SIGNAL FROM THE FACP. UPON ACTUATION OF AN AFFECTED ZONE FIRE ALARM FROM THE FACP, THE CONTROLLER SHALL INITIATE THE SHUTDOWN/STANDBY SEQUENCE. A MANUAL RESET SHALL BE REQUIRED PRIOR TO OPERATION FOLLOWING A FACP SHUTDOWN.

VARIABLE AIR VOLUME TERMINAL UNIT SCHEDULE																					
ID	MANUFACTURER	MODEL NO.	NECK SIZE	TYPE	PRIMARY AIRFLOW		HEATING COIL		HEATING ELEMENT		UNIT WEIGHT		DISCONNECT			REMARKS					
					MAX	MIN	DESCRIPTION	QTY	POWER	SCR	FLA	MCA	MOCP	VOLT	PH		FURNISH BY	INSTALL BY			
VAV-01	TITUS	DES-V	8"	SINGLE DUCT	400 CFM	120 CFM	Electric Heat	1	3.0 kW	Yes	68 lb	14.4 A	18.0 A	20.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-02	TITUS	DES-V	8"	SINGLE DUCT	400 CFM	120 CFM	Electric Heat	1	3.0 kW	Yes	68 lb	14.4 A	18.0 A	20.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-03	TITUS	DES-V	8"	SINGLE DUCT	600 CFM	180 CFM	Electric Heat	1	4.5 kW	Yes	68 lb	21.6 A	27.0 A	30.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-04	TITUS	DES-V	8"	SINGLE DUCT	400 CFM	120 CFM	Electric Heat	1	3.0 kW	Yes	68 lb	14.4 A	18.0 A	20.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-05	TITUS	DES-V	8"	SINGLE DUCT	400 CFM	120 CFM	Electric Heat	1	3.0 kW	Yes	68 lb	14.4 A	18.0 A	20.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-06	TITUS	DES-V	8"	SINGLE DUCT	300 CFM	90 CFM	Electric Heat	1	2.0 kW	Yes	68 lb	9.6 A	12.0 A	15.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-07	TITUS	DES-V	10"	SINGLE DUCT	1,100 CFM	330 CFM	Electric Heat	1	8.0 kW	Yes	81 lb	41.8 A	52.0 A	60.0 A	208 V	3	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3
VAV-08	TITUS	DES-V	8"	SINGLE DUCT	400 CFM	120 CFM	Electric Heat	1	3.0 kW	Yes	68 lb	14.4 A	18.0 A	20.0 A	208 V	1	DIV. 23	DIV. 23	NFS	DIV. 26	1,2,3

- NOTES:
- PROVIDE MODEL SELECTED OR EQUIVALENT BY CARRIER.
 - PROVIDE UNIT WITH SINGLE POINT POWER CONNECTION.
 - PROVIDE WITH MANUFACTURER CONTROLS STRATEGY TO INTEGRATE VAVS TO RTU.

SPLIT SYSTEM HEAT PUMP SCHEDULE																											
ID	MANUFACTURER	MODEL NO.	TYPE	EVAPORATOR COIL		HEATING COIL		COMPRESSOR			REFRIGERANT			MOTOR		SUMMER AMBIENT DBT		WINTER AMBIENT DBT		UNIT WEIGHT		DISCONNECT			INTERLOCK		NOTES
				TOTAL CAP	SENSIBLE CAP	HEATING CAP	CAP	TYPE	TYPE	CHARGE	QTY	RLA	FLA	MCA	MOCP	VOLT	PH	FURNISH BY	INSTALL BY								
HP-1	TRANE	4TWR060A	AIR COOLED HEAT PUMP	36,600 Bluh	45,443 Bluh	21,480 Bluh	5.0 ton	EFLX	R-410A	13 lb	1	15.3 A	95.0 °F	47.0 °F	17	3.5	293 lb	37.0 A	60.0 A	208 V	1	DIV. 26	AHU-1	1,2,3,4,5			1,2,3,4,5
HP-2	TRANE	4TWR0424	AIR COOLED HEAT PUMP	23,900 Bluh	17,900 Bluh	21,600 Bluh	2.0 ton	EFLX	R-410A	7 lb	1	10.9 A	95.0 °F	47.0 °F	14.5	3.5	216 lb	14.0 A	25.0 A	208 V	1	DIV. 26	AHU-2	1,2,3,4,5			1,2,3,4,5
HP-3	TRANE	4TWR026A1	AIR COOLED HEAT PUMP	24,500 Bluh	18,700 Bluh	15,000 Bluh	2.0 ton	EFLX	R-410A	10 lb	1	11.7 A	95.0 °F	47.0 °F	17	4.2	236 lb	15.0 A	25.0 A	208 V	1	DIV. 26	AHU-3	1,2,3,4,5			1,2,3,4,5
HP-4	TRANE	4TWR036A	AIR COOLED HEAT PUMP	36,600 Bluh	28,000 Bluh	21,600 Bluh	1.0 ton	EFLX	R-410A	9 lb	1	15.3 A	95.0 °F	47.0 °F	17	3.9	210 lb	21.0 A	35.0 A	208 V	1	DIV. 26	AHU-4	1,2,3,4,5			1,2,3,4,5
MSPH-1	TRANE	TRU2A0121A708A	AIR COOLED HEAT PUMP	12,000 Bluh	18,000 Bluh	18,000 Bluh	1.0 ton	SCROLL	R-410A	4 lb	1	17.0 A	95.0 °F	47.0 °F	20	3.4	93 lb	11.0 A	25.0 A	208 V	1	DIV. 26	MAHU-1	1,2,3,4,5,6			1,2,3,4,5,6

- NOTES:
- PROVIDE MODEL SELECTED OR EQUIVALENT BY DAIKIN. EQUIVALENT TRANE / MITSUBISHI UNITS APPROVED.
 - THE INSTALLER SHALL BE CERTIFIED BY THE EQUIPMENT MANUFACTURER AND SHALL PROVIDE REFRIGERANT PIPING SIZED PER MANUFACTURER INSTALLATION INSTRUCTIONS.
 - PROVIDE WITH HIGH PERFORMANCE HEATING MODE.
 - PROVIDE WITH TAMPER RESISTANT LOCKING REFRIGERANT CONNECTIONS.
 - INSULATE EXTERIOR REFRIGERANT LINES WITH 1.5" ELASTOMERIC INSULATION WITH ALUMINUM JACKET EQUIVALENT TO K-FLEX CLAD AL WITH K-FLEX CLAD AL TAPE.
 - OUTDOOR UNIT POWERS INDOOR UNIT.

GRILLES, REGISTERS AND DIFFUSERS SCHEDULE																							
ID	DESCRIPTION	MANUFACTURER	MODEL	QTY	SYSTEM	FACE SIZE			NECK			BLADE DESIGN			INSTALLATION			OPTIONS			SPECIFICATION	NOTES	
						SIZE	SIZE	WIDTH	HEIGHT	THICKNESS	SPACING	SINGLE	DOUBLE	ORIENTATION	BORDER TYPE	DAMPER DESCRIPTION	FILTER DESCRIPTION	EQUALIZING GRID	HEAVY DUTY FRAME				
RD1	PERFORATED DIFFUSER WITH DEFLECTORS	Titus	PAR-AA	5	RIA	24x24	12"		10"	6"	1/8"	1/2"	35.0°		LONG	TYPE 1 (SURFACE)	---	No				PERFORATED DIFFUSER WITH FACE MOUNTED DEFLECTORS	1,2,3,4
RG1	LOUVERED GRILLE	Titus	35FL	1	RIA				12"	6"	1/8"	1/2"	35.0°		LONG	TYPE 1 (SURFACE)	---	No				LOUVERED FACE DIFFUSER	1,2,3,4
RG1	LOUVERED GRILLE	Titus	35FL	3	RIA				14"	6"	1/8"	1/2"	35.0°		LONG	TYPE 1 (SURFACE)	---	No				LOUVERED FACE DIFFUSER	1,2,3,4
RG1	LOUVERED GRILLE	Titus	35FL	3	RIA				24"	<varies>	1/8"	1/2"	35.0°		LONG	TYPE 1 (SURFACE)	---	No				LOUVERED FACE DIFFUSER	1,2,3,4
RG2	LOUVERED FILTER GRILLE	Titus	35FLF	2	RIA				24"	<varies>	1/8"	1/2"	35.0°		LONG	TYPE 1 (SURFACE)	---	1" FILTER				LOUVERED FILTER FACE DIFFUSER	1,2,3,4
SD1	3-CONE DIFFUSER	Titus	TMS-AA	15	S/A	24x24	6"								TYPE 3 (LAY-IN)	---	No					HIGH PERFORMANCE 3-CONE DIFFUSER	1,2,3,4
SD1	3-CONE DIFFUSER	Titus	TMS-AA	6	S/A	24x24	8"								TYPE 3 (LAY-IN)	---	No					HIGH PERFORMANCE 3-CONE DIFFUSER	1,2,3,4
SD1	3-CONE DIFFUSER	Titus	TMS-AA	2	S/A	24x24	10"								TYPE 3 (LAY-IN)	---	No					HIGH PERFORMANCE 3-CONE DIFFUSER	1,2,3,4
SD1	3-CONE DIFFUSER	Titus	TMS-AA	1	S/A	24x24	12"								TYPE 3 (LAY-IN)	---	No					HIGH PERFORMANCE 3-CONE DIFFUSER	1,2,3,4
SD2	ROUND DIFFUSER WITH ADJUSTABLE PATTERNS	Titus	TRM-AA	17	S/A	---	10"								SURFACE	---	No					ROUND DIFFUSER WITH TWO DISCHARGE PATTERNS	1,2,3,4
SG1	LOUVERED DOUBLE DEFLECTION GRILLE	Titus	300FL	4	S/A				10"	6"	1/8"	3/4"	0.0°	0.0°	DOUBLE LONG	TYPE 3 (LAY-IN)	---	No				LOUVERED FACE DIFFUSER	1,2,3,4
SG1	LOUVERED DOUBLE DEFLECTION GRILLE	Titus	300FL	1	S/A				14"	6"	1/8"	3/4"	0.0°	0.0°	DOUBLE LONG	TYPE 1 (SURFACE)	---	No				LOUVERED FACE DIFFUSER	1,2,3,4

- NOTES:
- PROVIDE MODEL SPECIFIED OR APPROVED EQUAL BY PRICE, NALOR, KRUEGER, METALARE, OR TUTTLE & BAILEY.
 - PROVIDE WITH ALUMINUM CONSTRUCTION AND STANDARD FINISH.
 - COLOR BY ARCHITECT. PROVIDE SELECTION OPTIONS.
 - PROVIDE WITH OPTIONAL SURFACE MOUNT KIT AS REQUIRED.

WALL MOUNTED HEAT PUMP SCHEDULE																	
ID	MANUFACTURER	MODEL NO.	TYPE	FAN		COOLING COIL		HEATING COIL		FILTER		INTERLOCK		NOTES			
				DESIGN AIRFLOW	MOTOR	NOMINAL CAP	ARISIDE	HEATING CAP	EFF	UNIT WEIGHT	VOLT	ID					
MAHU-1	TRANE	TPKAD0121LADA	DUCTLESS AC UNIT	400 CFM	1	30.0 W	Yes	1.0 ton	12,000 Bluh	80.0 °F	60.0 °F	18,000 Bluh	30%	29 lb	24 V	MSPH-1	1,2

- NOTES:
- PROVIDE MODEL SELECTED OR EQUIVALENT.
 - PROVIDE A 7-DAY PROGRAMMABLE THERMOSTAT.

AIR HANDLING UNIT SUMMARY SCHEDULE																						
ID	MANUFACTURER	MODEL NO.	SUPPLY AIRFLOW	OUTSIDE AIR		FAN		COOLING COIL			HEATING COIL		HEATING ELEMENT		FILTER		UNIT WEIGHT		DISCONNECT			NOTES
				FLOW	DESCRIPTION	QTY	POWER	DESCRIPTION	CAP	TOTAL	SENSIBLE	CAP	POWER	TYPE	EFF	WEIGHT	MCA	MOCP	VOLT	PH	FURNISH BY	
AHU-1	TRANE	TAM9AC06V51	1,950 CFM	300 CFM	Supply Fan	1	1.00 hp	Evaporator Coil	5.0 ton	56,784 Bluh	45,443 Bluh	36,985 Bluh	7 kW	PLEATED	MERV-8	163 lb	51.0 A	60.0 A	208 V	1	DIV. 26	1,2,3,4,5,6
AHU-2	TRANE	GAMB0824	600 CFM	0 CFM	Supply Fan	1	0.33 hp	Evaporator Coil	2.0 ton	28,900 Bluh	21,900 Bluh	18,400 Bluh	6 kW	PLEATED	MERV-8	132 lb	38.0 A	40.0 A	208 V	1	DIV. 26	1,2,3,4,5,6
AHU-3	TRANE																					

GENERAL MECHANICAL SYMBOLS	
	REVISION NUMBER - SHOWN ON PLANS
	POINT WHERE NEW CONNECTS TO EXISTING
	NUMBER OF DETAIL ON SHEET
	NUMBER OF SHEET WHERE DETAIL APPEARS
	KEYNOTE
	CONTINUATION SYMBOL
	ROOM NAME AND NUMBER
	ITEM TO BE DEMOLISHED
	AREA NOT IN CONTRACT
	PIPE SIZE TAG (DIAMETER)
	ABOVE GROUND PIPING
	BELOW GROUND PIPING
	PIPE SLOPE TAG
	PIPE INVERT ELEVATION TAG
	EXISTING PIPE TAG
	PIPING BEING DEMOLISHED


ABBREVIATIONS			
Ø	ROUND	LPG	LIQUEFIED PETROLEUM GAS
AV	AIR ADMITTANCE VALVE	LVR	LOUVER
ABV	ABOVE	LWT	LEAVING WATER TEMPERATURE
AC	AIR CONDITIONING	MA	MIXED AIR
AD	AREA DRAIN	MAX	MAXIMUM
ADD	ADDENDUM	MBH	ONE THOUSAND BTU PER HOUR
AF	ABOVE FINISHED FLOOR	MCF	ONE THOUSAND CUBIC FEET
AFUE	ANNUAL FUEL UTILIZATION EFFICIENCY	MD	MOTORIZED DAMPER
ALT	ALTERNATE	MECH	MECHANICAL
AP	ACCESS PANEL	MFR	MANUFACTURER
ARCH	ARCHITECT/ARCHITECTURAL	MN	MINIMUM
BFF	BELOW FINISHED FLOOR	MISC	MISCELLANEOUS
BLW	BELOW	MTR	MOTOR
BTU	BRITISH THERMAL UNITS	MUA	MAKE UP AIR
BTUH	BRITISH THERMAL UNITS PER HOUR	NC	NOISE CRITERIA
CAP	CAPACITY	NC	NORMALLY CLOSED
CB	CATCH BASIN	NC	NOT IN CONTRACT
CFM	CUBIC FEET PER MINUTE	NO	NUMBER
CLG	CEILING	NO	NORMALLY OPEN
CO	CLEAN OUT	NTS	NOT TO SCALE
CW	COLD WATER	O	OXYGEN
D	DEGREE	O/A	OUTSIDE AIR
DB	DRY BULB	ORD	OVERFLOW ROOF DRAIN
DA	DIAMETER	PD	PRESSURE DROP
DN	DOWN	PV	POST INDICATOR VALVE
DW	DISTILLED WATER	PLB	PLUMBING
EA	EACH	PRESS	PRESSURE
EAT	ENTERING AIR TEMPERATURE	PRV	PRESSURE REDUCING VALVE
ELEC	ELECTRICAL	PSI	POUNDS PER SQUARE INCH GAUGE
EQUIP	EQUIPMENT	PWIR	POWER
EWC	ELECTRIC WATER COOLER	R	DUCT RISER
EWT	ENTERING WATER TEMPERATURE	RA	RELATIVE HUMIDITY
EIA	EXHAUST AIR	RA	RELIEF AIR
EXIST	EXISTING	RM	ROOM
F	DEGREES FAHRENHEIT	RP	REVOLUTIONS PER MINUTE
FCO	FLOOR CLEAN OUT	RW	RAIN WATER
FD	FLOOR DRAIN	SF	SQUARE FOOT
FDC	FIRE DEPARTMENT CONNECTION	SIA	SUPPLY AIR
FL	FLOOR	SAN	SANITARY
FO	FUEL OIL	SF	SQUARE FOOT
FOV	FUEL OIL VENT	SM	SURFACE MOUNT
FOR	FUEL OIL RETURN	SP	STANDPIPE
FOS	FUEL OIL SUPPLY	SP	STATIC PRESSURE
FPM	FEET PER MINUTE	STM	STEAM
FS	FLOOR SINK	T	THERMOSTAT
FT	FOOT/FEET	TD	TEMPERATURE DROP
FTR	FIN TUBE RADIATION	TD	TRENCH DRAIN
GAL	GALLON	TEMP	TEMPERATURE
GF	GAS-FIRED	TR	TYPICAL
GC	GENERAL CONTRACTOR	UG	UNDERGROUND
GCO	GROUND CLEAN OUT	VAC	VACUUM
GM	GALLONS PER MINUTE	V	VENT
GW	GREASE WASTE	VAV	VARIABLE AIR VOLUME
HB	HOSE BIB	VENT	VENTILATION
HP	HORSE POWER	VTR	VENT THROUGH ROOF
HTG	HEATING	W	WASTE
HTR	HEATER	WB	WET BULB
HW	HOT WATER	WCO	WALL CLEAN OUT
HYD	HYDRANT	WH	WALL HYDRANT
ID	INDIRECT		
IN	INCH		
INV	INVERT		
LB	POUND		
LBHR	POUNDS PER HOUR		
LAT	LEAVING AIR TEMPERATURE		
LP	LOW PRESSURE		

EQUIPMENT ABBREVIATIONS			
ACU	AIR CONDITIONING UNIT	ET	EXPANSION TANK
ACCU	AIR COOLING CONDENSING UNIT	EWH	ELECTRIC WATER HEATER
AHU	AIR HANDLING UNIT	FCU	FAN COIL UNIT
AS	AIR SEPARATOR	FP	FIRE PUMP
B	BOLLER	GI	GREASE INTERCEPTOR
CH	CHILLER	GRV	GRAVITY ROOF VENTILATOR
CT	COOLING TOWER	HWP	HEATING WATER PUMP
CUH	CABINET UNIT HEATER	HRI	HEAT RECOVERY UNIT
CHWP	CHILLED WATER PUMP	PRV	POWER ROOF VENTILATOR
DBP	DOMESTIC WATER BOOSTER PUMP	RE	RETURN EXHAUST FAN
DC	DUCT MOUNTED COIL	RTU	ROOFTOP UNIT
DCP	DOMESTIC WATER CIRCULATING PUMP	SP	SUMP PUMP
ED	EXHAUST FAN	UH	UNIT HEATER
EDC	ELECTRIC DUCT COIL	WH	WATER HEATER

NOTE
ALL OF THE GENERAL NOTES ON THIS SHEET ARE TO BE APPLIED TO ALL OTHER DRAWINGS IN THIS SET. THE SYMBOLS AND ABBREVIATIONS SHOWN ON THIS SHEET MAY OR MAY NOT BE USED IN THIS SET OF DRAWINGS.

PLUMBING AND PIPING SYMBOLS	
	CHILLED WATER RETURN
	CHILLED WATER SUPPLY
	CONDENSATE DRAINAGE
	CONDENSER WATER RETURN
	CONDENSER WATER SUPPLY
	GEOTHERMAL WATER RETURN
	GEOTHERMAL WATER SUPPLY
	HEATING WATER RETURN
	HEATING WATER SUPPLY
	NATURAL GAS
	PROPANE GAS
	REFRIGERANT LIQUID
	REFRIGERANT SUCTION
	REFRIGERANT HOT GAS
	STEAM
	CONDENSATE RETURN
	COMBINATION WASTE & VENT
	COMPRESSED AIR
	DOMESTIC COLD WATER
	HARD COLD WATER
	SOFT COLD WATER
	FILTERED COLD WATER
	REVERSE OSMOSIS WATER
	HOT WATER
	HOT WATER 140°
	HOT WATER RECIRCULATION
	HOT WATER RECIRCULATION 140°
	GREASE VENT
	GREASE WASTE
	INDIRECT WASTE
	OIL VENT
	OIL WASTE
	PUMP DISCHARGE
	SANITARY SEWER
	SANITARY VENT
	SOLAR HOT WATER RETURN
	SOLAR HOT WATER SUPPLY
	STORM DRAINAGE
	OVERFLOW STORM DRAINAGE
	PIPE DROP
	PIPE RISE
	PIPE TEE
	PLUG
	REDUCING 45 DEGREE TEE
	45 DEGREE TEE

PIPE ACCESSORY TAGS			
	2" DOM WM DOMESTIC WATER METER		2" M CNTR MOTORIZED CONTROL VALVE
	2" BALANCING BALANCING VALVE		2" 3 WAY MTRZD CONTROL VALVE
	2" SHUTOFF 1/4 TURN BALL VALVE		2" PRV PRESSURE REDUCING VALVE
	2" CHECK CHECK VALVE		3/8" SOLENOID REFRIGERANT SOLENOID VALVE
	2" TMV 3-WAY MIXING VALVE		2" BUTTERFLY BUTTERFLY VALVE
	3-WAY AIRMOTOR CONTROLLER		LOCK SHIELD VALVE
	ANGLE GLOBE VALVE		PLUG VALVE
	ANGLE HOSE VALVE		QUICK OPENING VALVE
	DIAPHRAGM VALVE		SPRING CHECK VALVE
	GLOBE VALVE		SWING GATE CHECK VALVE
	HOSE GLOBE VALVE		TEMP PRESSURE RELIEF VALVE







PROJECT GENERAL NOTES


- LOCATIONS OF PIPING, DUCTWORK AND EQUIPMENT AS INDICATED ON THE DRAWING, ARE APPROXIMATE AND SUBJECT TO MINOR ADJUSTMENTS IN THE FIELD. WORK SHALL BE COORDINATED WITH ALL OTHER TRADES TO AVOID INTERFERENCE IN THE FIELD.
- CONTRACTOR SHALL OBTAIN AND PAY FOR ALL NECESSARY PERMITS AND SHALL ARRANGE FOR ALL INSPECTIONS AS REQUIRED.
- PRIOR TO STARTING WORK, SUBMIT SHOP DRAWINGS FOR ALL MECHANICAL EQUIPMENT, PLUMBING FIXTURES, AND DIFFUSERS.
- PROVIDE ONE YEAR WARRANTY FOR ALL WORKMANSHIP AND MATERIALS AFTER THE DATE OF FINAL ACCEPTANCE.
- COORDINATE INSTALLATION OF PIPING, DUCTWORK, CONDUIT, LIGHTS, CABLE TRAY, STRUCTURE, AND EQUIPMENT TO PREVENT CONFLICTS.
- FINAL PRODUCT SHALL BE A COMPLETE AND FUNCTIONING SYSTEM, AND SHALL CONFORM TO ALL REQUIREMENTS OF APPLICABLE FEDERAL, STATE, AND LOCAL CODES, INCLUDING BUT NOT LIMITED TO THE INTERNATIONAL BUILDING CODE AND INTERNATIONAL MECHANICAL CODE.
- INSTALL ALL EQUIPMENT IN ACCORDANCE WITH THE RESPECTIVE MANUFACTURERS' WRITTEN INSTALLATION INSTRUCTIONS, AT A LEVEL OF QUALITY AND WORKMANSHIP CONSISTENT WITH THE SPECIFICATIONS.
- PROVIDE SLEEVES AND/OR OPENINGS TO RUN PIPES AND DUCTS THROUGH FOUNDATIONS, FLOORS, WALLS, AND ROOF.
- PENETRATIONS OF RATED ASSEMBLIES SHALL BE FIRE STOPPED. FIRE STOPPING SHALL BE AN APPROVED MATERIAL AS PRESCRIBED IN CSFM STANDARD 43-1 AND SHALL BE U.L. LISTED.
- ADJUST PIPING AND DUCTWORK SIZES TO PROPERLY CONNECT TO MECHANICAL EQUIPMENT.
- FOR DETAILS, EQUIPMENT CONNECTIONS, AND PIPE SIZES NOT SHOWN ON THE SECTIONS, REFER TO DETAILS, SCHEDULES, AND SPECIFICATIONS.
- INSTALL EXPOSED PIPING AND DUCTWORK AS HIGH AS PRACTICAL IN ROOMS WITHOUT CEILINGS.
- PIPE SIZES SHOWN SHALL BE CONTINUED IN THE DIRECTION OF FLOW UNTIL ANOTHER SIZE IS SHOWN.
- LOCATE DUCTWORK, PIPING AND MECHANICAL EQUIPMENT AWAY FROM THE SPACE ABOVE ELECTRICAL PANELS, TRANSFORMERS AND OTHER ELECTRICAL EQUIPMENT.
- MAINTAIN CLEAR ACCESS TO SERVICE EQUIPMENT AND OTHER ACCESSORIES REQUIRING SERVICE, VISUAL INSPECTION OR HAND OPERATION, WHERE INDICATED OR REQUIRED. PROVIDE ACCESS PANELS OF THE TYPE SELECTED TO FIT MATERIALS IN WHICH INSTALLED.
- ALL ROOF MOUNTED EQUIPMENT SHALL BE A MINIMUM 10" FROM EDGE OF ROOF.
- REMOVE ALL UNUSED PIPING, DUCTWORK AND ACCESSORIES.
- THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE FOR FIELD VERIFYING, PRIOR TO FINAL BID, ALL EXISTING CONDITIONS FOR PLUMBING AND MECHANICAL SYSTEMS WITHIN TENANT SPACE AND WITHIN CLOSE PROXIMITY OF TENANT SPACE.
- THE MECHANICAL CONTRACTOR SHALL PERFORM SERVICE AND REPAIR ON THE EXISTING EQUIPMENT AND ITS ACCESSORIES AS FOLLOWS: CLEAN ALL COILS, REPLACE THE FILTERS AND BELTS, INSPECT, REPAIR, OR REPLACE THE ECONOMIZERS, DRIVES AND FAN BEARINGS, MOTORS, CONTROL COMPONENTS, VALVES AND ANY OTHER ITEM NECESSARY FOR A COMPLETE AND PROPER OPERATING SYSTEM. THIS CONTRACTOR SHALL ALSO VISIT THE SITE, PRIOR TO FINAL BIDDING, AND VERIFY ALL EXISTING SITE CONDITIONS. PROVIDE ALL MATERIAL AND COMPONENTS AS NEEDED TO BRING THE UNITS TO FULL COMPLIANCE OF THE LANDLORD'S CRITERIA AND LOCAL AUTHORITY HAVING JURISDICTION.
- WHERE FLOOR DRAINS OCCUR WITHIN THE LIMITS OF CONSTRUCTION, PREVENT CONSTRUCTION DEBRIS FROM ENTERING DRAIN BODY BY SEALING DRAIN OPENING PRIOR TO START OF WORK. UNSEAL DRAINS AT COMPLETION OF CONSTRUCTION.
- THE CONTRACTOR SHALL BE FAMILIAR WITH ALL THE CONDITIONS BOTH EXISTING AND THOSE ILLUSTRATED BY THESE DOCUMENTS AS WELL AS THOSE WHICH CAN BE REASONABLY ANTICIPATED INCLUDING, BUT NOT LIMITED TO ARCHITECTURAL, ELECTRICAL, VENTILATION, PLUMBING, AND OTHER SYSTEMS INVOLVED ON THIS PROJECT.
- LOCATE EQUIPMENT REQUIRING ACCESS 2'-0" MAXIMUM ABOVE CEILING.
- REFER TO HVAC SECTIONS FOR GAS AND A.C. CONDENSATE DRAIN PIPING.
- ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE CURRENT EDITION OF ALL APPLICABLE CODES AND LOCAL CODES AS APPLIED BY THE AUTHORITY HAVING JURISDICTION.
- THE CONTRACTOR'S WORK SCHEDULE SHALL BE SUBMITTED TO AND APPROVED BY THE OWNER.

PLUMBING GENERAL NOTES


- PROVIDE ALL MATERIALS AND LABOR NECESSARY FOR COMPLETE AND PROPERLY FUNCTIONING PLUMBING SYSTEMS.
- WORK SHALL CONFORM TO OR MEET THE REQUIREMENTS OF THE MOST CURRENT EDITION OF INTERNATIONAL PLUMBING CODE AND FEDERAL, STATE AND LOCAL CODES AND ORDINANCES WHICH APPLY TO THIS WORK.
- DRAWING IS DIAGRAMMATIC IN NATURE AND IS NOT INTENDED TO BE SCALED FOR DIMENSIONS.
- ALL MATERIALS SHALL MEET THE REQUIREMENTS OF UL WHERE UL STANDARDS ARE ESTABLISHED FOR THOSE ITEMS. ALL ITEMS SHALL BE CLASSIFIED BY UL AS SUITABLE FOR THE PURPOSE USED.
- ALL ITEMS SHALL BE NEW AND ALL MATERIAL, EQUIPMENT AND DEVICES SHALL BE CURRENT PRODUCTS BY MANUFACTURERS REGULARLY ENGAGED IN THE PRODUCTION OF SUCH PRODUCTS.
- COORDINATE LOCATION OF PLUMBING WORK WITH OTHER TRADES TO AVOID CONFLICTS AND INTERFERENCES.
- INSTALL ALL EQUIPMENT AND MATERIALS IN ACCORDANCE WITH MANUFACTURERS' INSTRUCTIONS AND RECOMMENDATIONS.
- COORDINATE AND OBTAIN PERMITS AND INSPECTIONS FROM AUTHORITY HAVING JURISDICTION.
- PROVIDE OWNER WITH CERTIFICATE OF FINAL INSPECTION AND ACCEPTANCE FROM AUTHORITY HAVING JURISDICTION.
- CLEANOUTS SHALL BE LINE SIZE UNLESS NOTED OTHERWISE.
- FLOOR DRAINS SHALL BE LINE SIZE UNLESS NOTED OTHERWISE. THE FLOOR DRAIN SHALL BE FLUSH MOUNTED WITH FINISHED FLOOR AND THE FLOOR SHALL SLOPE TO THE DRAINS AN A MINIMUM OF 1/16" PER FOOT.
- VALVES SHALL BE LINE SIZE UNLESS NOTED OTHERWISE.
- ABOVE GROUND WATER PIPING SHALL BE TYPE L COPPER. UNDERGROUND WATER PIPING SHALL BE TYPE K COPPER.
- COLD AND HOT WATER VALVES 2" AND SMALLER SHALL BE RATED FOR POTABLE, BALL MSS SP-110 BALL VALVE SHALL BE FULL PORT THREE PIECE OR TWO PIECE WITH A UNION DESIGN WITH ADJUSTABLE STEM PACKAGE. THREADED STEM 150 PSIG AND A CWP RATING OF 400 PSIG. THE BODY MATERIAL SHALL BE BRONZE ASTM B584, ALLOY C84. THE ENDS SHALL BE NON-LEAD SOLDER.
- ALL WASTE, DRAIN AND VENT PIPING SHALL BE STANDARD WEIGHT, TYPE 1 PVC INSTALLED IN ACCORDANCE WITH ASTM D2221.
- COLD WATER PIPING SHALL BE INSULATED WITH 1" THICK GLASS FIBER (K OF 0.24 AT 75F) WITH VAPOR BARRIER. HOT WATER PIPING SHALL BE INSULATED WITH 1 1/2" THICK GLASS FIBER (K OF 0.24 AT 75F) WITHOUT VAPOR BARRIER.
- HANGERS FOR PIPE 1/2" TO 1 1/2" SHALL BE CARBON STEEL ADJUSTABLE SWIVEL SPLIT RING TYPE, WITH A MAXIMUM SPACING OF 8' 0" ON CENTERS. HANGERS FOR 2" AND LARGER SHALL BE CARBON STEEL ADJUSTABLE CLEVIS TYPE. HANGER SPACING FOR PIPES 2 1/2" AND SMALLER SHALL NOT EXCEED 10' 0" ON CENTERS. PROVIDE CLEARANCE IN HANGERS FROM STRUCTURES AND OTHER EQUIPMENT FOR INSTALLATION OF INSULATION AND ACCESS TO VALVES AND FITTINGS. INSTALL HANGERS WITHIN 5'-0" OF ALL CHANGES IN DIRECTION OF PIPING.
- ALL ROOF PENETRATIONS SHALL BE COORDINATED WITH ROOFING CONTRACTOR TO ENSURE ROOF BOND WILL BE MAINTAINED.
- PROVIDE ALL OPERATION AND MAINTENANCE MANUALS FOR PLUMBING EQUIPMENT TO BUILDING OWNER.

PLUMBING SHEET INDEX			
SHEET	DESCRIPTION	REV NO.	DATE
PL001	PLUMBING TITLE SHEET	0	10/25/2021
FD-01	FIRST FLOOR PLUMBING DEMOLITION PHASING PLAN	0	10/25/2021
P1-01	FIRST FLOOR PHASE 1 MEDICAL AREA PLUMBING PLAN	0	10/25/2021
P1-02	FIRST FLOOR PHASE 1 RESTROOM PLUMBING PLAN	0	10/25/2021






1 FIRST FLOOR PHASE 1 OVERALL PLUMBING PLAN
3/32" = 1'-0"



2 FIRST FLOOR PHASE 1 ENLARGED DOMESTIC PLUMBING PLAN
1/4" = 1'-0"




3 FIRST FLOOR PHASE 1 ENLARGED WASTE AND VENT PLUMBING PLAN
1/4" = 1'-0"


KEYNOTES
1 PROVIDE CAP ON SS BELOW SLAB FOR COVERING CONNECTION FOR PHASE 2

ID	FLOOR	DESCRIPTION	MANUFACTURER	MODEL	FINISH	TRIM		WASTE ROUGH-IN PIPE SIZE	VENT PIPE SIZE	COLD WATER ROUGH-IN PIPE SIZE	HOT WATER ROUGH-IN PIPE SIZE	SPECIFICATION
						MANUFACTURER	MODEL					
EWC-1	FIRST	WATER COOLER - DUAL HEIGHT	ELKAY	EZSTLWSSK	STAINLESS STEEL CABINET			2"	1 1/2"	1/2"		TWO LEVEL WALL HUNG WATER COOLER WITH BOTTLE FILLING STATION. THE UNIT SHALL BE COMPLETE WITH CABINET, MOUNTING FRAME, SELF CLOSING EASY TOUCH SIDE AND FRONT PUSHBAR CONTROLS, FLEXIGUARD SAFETY BUBBLER, REFRIGERATING SYSTEM, AIR COOLED, 120 VOLT, 60 CYCLE, SINGLE PHASE POWER CONNECTION, FULLY AUTOMATIC, COMPLETE AND READY TO OPERATE.
FD-1	FIRST	FLOOR DRAIN	WATTS	FD-100-A				3"	2"			EPOXY COATED CAST IRON FLOOR DRAIN WITH ANCHOR FLANGE, REVERSIBLE CLAMPING COLLAR WITH PRIMARY & SECONDARY VEEHOLES, ADJUSTABLE ROUND HEEL, PROOF NICKEL BRONZE STRAINER, AND NO HUB OUTLET.
JS-1	FIRST	JANITOR SINK	FIAT	MSB-2424		FIAT	830AA	3"	2"	3/4"	3/4"	SERVICE BASIN WITH CAP ON TWO SIDES, WITH CHROME PLATED 3" DRAIN AND CAST IRON TRAP. FAUCET SHALL INCLUDE PAIL HOOK AND ATMOSPHERIC VACUUM BREAKER SPOUT. FURNISH MOP HANGER AND HOSE BRACKET.
LAV-1A	FIRST	LAVATORY - WALL HUNG - ADA	ZURN	Z5340	WHITE	ZURN	Z7440-XL	2"	1 1/2"	1/2"	1/2"	WALL HUNG LAVATORY WITH BACKSPLASH, FAUCET HOLES ON 4" CENTERS, ZURN HARDWIRED Z6915-XL DECK MOUNTED FAUCET, GRID DRAIN, LOOSE KEY ANGLE STOPS AND SUPPLIES. INSULATE WATER AND WASTE WITH ADA INSULATION KIT. MOUNT AT ADA COMPLIANT HEIGHT.
LAV-2	FIRST	LAVATORY - COUNTER	ZURN	Z5110	WHITE	ZURN	Z4915-XL	2"	1 1/2"	1/2"	1/2"	COUNTERTOP LAVATORY, SELF-RIMMING, FAUCET HOLES ON 4" CENTERS, ZURN HARDWIRED Z6915-XL DECK MOUNTED FAUCET, GRID DRAIN, LOOSE KEY ANGLE STOPS AND SUPPLIES. INSULATE WATER AND WASTE WITH INSULATION KIT.
LAV-2A	FIRST	LAVATORY - COUNTER - ADA	ZURN	Z5110	WHITE	ZURN	Z4915-XL	2"	2"	1/2"	1/2"	COUNTERTOP LAVATORY, SELF-RIMMING, FAUCET HOLES ON 4" CENTERS, ZURN HARDWIRED Z6915-XL DECK MOUNTED FAUCET WITH SENSOR, HARDWIRED POWER, GRID DRAIN, LOOSE KEY ANGLE STOPS AND SUPPLIES. MOUNT AT ADA COMPLIANT HEIGHT. INSULATE WATER AND WASTE TO MEET ADA REQUIREMENTS USING ADA INSULATION KIT.
OB-1	FIRST	ICE MAKER OUTLET BOX	WATERTITE	AB9700-4A	WHITE					1/2"		FULLY RECESSED ICE MAKER SUPPLY BOX WITH COVER. PROVIDE 1/4" TURN BALL VALVES AND WATER HAMMER ARRESTORS IN BOX.
S-1	FIRST	SINGLE BOWL SINK	ELKAY	LRAD21995-3	STAINLESS STEEL	ELKAY	LKD2423BHC	2"	2"	1/2"	1/2"	SINGLE COMPARTMENT ADA COMPLIANT, SELF-RIMMING, 18 GAUGE, SINGLE LEVER SWIVEL FAUCET. ONE ELKAY MODEL NO. LK85 BASKET STRAINER, P-TRAP, TAILPIECES, SUPPLIES AND STOPS. INSULATE WATER AND WASTE TO MEET ADA REQUIREMENTS.
U-1	FIRST	URNAL	ZURN	Z5755-U	WHITE	ZURN	Z6003AV	2"	1 1/2"	3/4"		WALL HUNG URINAL WITH WASHOUT ACTION, TOP SPUD, SIZE 18" WITH INTEGRAL EXTENDED SHIELDS SUPPORTED BY THROUGH GOING BOLTS AND C.P. NUTS. ZEM56000-IS HARDWIRED SENSOR FLUSHMETER.
U-1A	FIRST	URNAL - ADA	ZURN	Z5755-U	WHITE	ZURN	Z6003AV	2"	1 1/2"	3/4"		WALL HUNG URINAL WITH WASHOUT ACTION, TOP SPUD, SIZE 18" WITH INTEGRAL EXTENDED SHIELDS SUPPORTED BY THROUGH GOING BOLTS AND C.P. NUTS. ZEM56000-IS HARDWIRED SENSOR FLUSHMETER.
WC-1A	FIRST	WATER CLOSET - FLOOR - FLUSH VALVE - ADA	ZURN	Z5668-BWL1	WHITE	ZURN	Z6000AV	3"	2"	1"		ELONGATED FLOOR MOUNTED WATER CLOSET, 1-1/2" TOP SPUD, WITH CHURCH 295GT ELONGATED OPEN FRONT SEAT. ZURN ZEM56000AV-IS HARDWIRED FLUSHMETER. INSTALL AT ADA COMPLIANT HEIGHT.
WC-2	FIRST	WATER CLOSET - FLOOR - FLUSH VALVE	ZURN	Z5654-BWL1	WHITE	ZURN	Z6000AV	3"	2"	1"		ELONGATED FLOOR MOUNTED WATER CLOSET, 1-1/2" TOP SPUD, WITH CHURCH 295GT ELONGATED OPEN FRONT SEAT. ZURN ZEM56000AV-IS HARDWIRED FLUSHMETER.

NOTES:
1. CONTRACTOR SHALL PROVIDE HARDWIRED POWER SUPPLY, MINI JUNCTION BOX FOR EACH GROUPING OF 8 HARDWIRED FIXTURES. COORDINATE WITH ELECTRICAL CONTRACTOR FOR 120VAC POWER AND CONNECTIONS TO 120V. PLUMBING CONTRACTOR SHALL PROVIDE AND ROUTE ALL LOW VOLTAGE WIRING IN A CONCEALED LOCATION.




Renovations of
Baywood
Technology &
Community Center
247 Grammar Lane,
Galax, VA 24333




These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
© 2021, WM2A Architects/Engineers, Inc.
All rights reserved. These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.
Project Status:
ISSUE FOR CONSTRUCTION
Revision No. (if any): 0
Revision Date: 10/25/2021
Project No.: 210063
Current Date: 10/25/2021
Drawing Name: FIRST FLOOR PHASE 1 MEDICAL AREA PLUMBING PLAN
Drawing No.: P1-01

KEYNOTES	
1	PROVIDE SHUTOFF VALVES IN VERTICALS BETWEEN THE FLOORS.
2	RECONNECT EXISTING EXTERIOR HOSE BIBB TO NEW 2" DCW MAIN.


ID	MANUFACTURER	MODEL NO.	TYPE	ELECTRIC HEAT EXCHANGER				FLA	MCA	MOCP	VOLT	PH	REMARKS
				HEATING CAP	STORAGE	RECOVERY	MAX TEMP						
				5.0 KW	25.0 gal/h	50.0 gal	80 °F						
WH-1	AO SMITH	DEN-52	STORAGE	5.0 KW	25.0 gal/h	50.0 gal	80 °F	24.0 A	30.0 A	35.0 A	208 V	1	PROVIDE WITH MINIMUM 2.0 GALLON ACCEPTANCE VOLUME EXPANSION TANK
WH-2	AO SMITH	DEN-40	STORAGE	5.0 KW	25.0 gal/h	40.0 gal	80 °F	24.0 A	30.0 A	35.0 A	208 V	1	PROVIDE WITH MINIMUM 2.0 GALLON ACCEPTANCE VOLUME EXPANSION TANK




1 FIRST FLOOR PHASE 1 OVERALL RESTROOMS PLUMBING PLAN
3/32" = 1'-0"




4 RESTROOMS DOMESTIC WATER RISER DIAGRAM
NOT TO SCALE



2 FIRST FLOOR PHASE 1 ENLARGED RESTROOMS DOMESTIC PLUMBING PLAN
1/4" = 1'-0"



3 FIRST FLOOR PHASE 1 ENLARGED RESTROOM WASTE AND VENT PLUMBING PLAN
1/4" = 1'-0"



5 RESTROOMS WASTE & VENT RISER DIAGRAM
NOT TO SCALE



Renovations of
Baywood
Technology &
Community Center
247 Grammar Lane,
Galax, VA 24333

KEYNOTES

- 1 SAWCUT FLOOR TO ACCOMMODATE NEW PLUMBING FIXTURES. COORDINATE FINAL CUT WITH THE GENERAL CONTRACTOR.
- 2 REMOVE ALL PLUMBING FIXTURES. REMOVE DOMESTIC HOT AND COLD WATER AND VENT PIPING BACK TO MAIN AND CAP AS CLOSE AS POSSIBLE AT MAIN. DEMOLISH SANITARY PIPING TO BELOW SLAB AND CAP.




ARCHITECTS
WM2A.COM
403B NORTH MAIN ST
HILLSVILLE, VA 24343



1 FIRST FLOOR PLUMBING DEMOLITION PLAN
PD1-01
1/8" = 1'-0"

Renovations of
Baywood
Technology &
Community Center
247 Grammar Lane,
Galax, VA 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.


© 2021, WM2A Architects/Planners, Inc.
All rights reserved.
These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status:
ISSUE FOR CONSTRUCTION
Revision No. (if any): 0 Revision Date: 10/25/2021
Project No.: 210063 Current Date: 10/25/2021
Drawing Name:

FIRST FLOOR PLUMBING
DEMOLITION PHASING PLAN
Drawing No. **PD1-01**

Baywood

Electrical & Fire Alarm Plans



ELECTRICAL SPECIFICATIONS:

PART ONE - GENERAL

The Electrical Contractor shall provide all labor, materials, and equipment, and perform all operations necessary for the installation of complete electrical work to meet the intent of, and as indicated on the drawings. Specific items and materials may or may not be addressed in specifications and drawings.

ELECTRICAL CONTRACTOR QUALIFICATIONS: Bidding electrical contractors must have sufficient general knowledge and experience to anticipate the needs of construction of this nature. The Electrical Contractor shall furnish all items required to complete the construction in accordance with reasonable interpretation of the intent of the drawings and specifications.

CODE REQUIREMENTS: All work shall be in accordance with the current State Building Code, local codes, NFPA, Current NEC and all other applicable codes and requirements of the local inspector. These code standards are not acceptable alternatives to reduce the standards or requirements outlined in these plans and specifications. All applicable "OSHA" regulations must be followed while performing this work.

NOTICE TO BIDDERS: Instructions to Bidders, Contract documents, and drawings are all parts of these specifications. The Electrical Contractor shall visit the site to familiarize themselves with existing conditions and the area in which the work is to be performed. The Electrical Contractor shall satisfy himself regarding subsoil conditions for excavations prior to making a proposal. The Electrical Contractor shall review and coordinate electrical service delivery with the electric utility. The Electrical Contractor must include in his bid the fees associated with temporary electrical service and permanent electrical and telephone service installation. This includes any fees to extend electrical and telephone service to the location of this project. Electrical Contractor must also review architectural, mechanical, plumbing, and civil drawings for electrical coordination.

ELECTRICAL PERMITS: Any permits, fees, inspection, and/or test charges required for the electrical work shall be secured and paid for by the Electrical Contractor.

SUBMITTALS: The Contractor shall submit (6) copies of shop drawings or submittal data on the luminaries and the panel board. Submittals shall be checked by the Electrical Contractor for conformance to the plans and specifications prior to being forwarded to the Engineer, and shall bear evidence of said review. Manufacturers and models shown in the schedules are intended to establish a standard of performance, efficiency, appearance, and quality. Any substitutions must meet these standards and be approved by the engineer before installation. All equipment and materials shall be installed in accordance with the recommendations of the manufacturer. Any indications in plans or specifications to the contrary shall be clarified with the Engineer, and any additional cost resulting from a substitution of equipment or material or from a manufacturer's installation requirement shall be paid for by the Electrical Contractor.

DRAWINGS: The drawings are diagrammatic only and are not intended to show minor details and exact locations. Locations of pipes, electrical switches, panels, equipment, luminaries, etc. shall be adjusted to accommodate the work to interferences anticipated and encountered. Equipment whose elevations cannot be changed shall have the right-of-way.

POWER WIRING: The Electrical Contractor shall provide all power wiring including disconnects, overload starters, fuses, breakers, line voltage control wiring, and final connections to the various electrical equipment. The HVAC Contractor shall be responsible for all controls, interlocks, low voltage control wiring and conduit for the HVAC equipment. All disconnects are to be fusible. Mechanical and plumbing contractors to provide single point of connection.

COORDINATION: The Electrical Contractor shall review drawings, specifications, and shop drawings provided by other trades to see if there are any conflicts. If conflicts are determined, then contact the architect/engineer for instructions.

WORKMANSHIP: Exposed work shall be square and plumb with adjacent surfaces and lines shall be neat and uniform in appearance. Conduit, junction boxes, and outlet boxes for switches and receptacles shall be recessed and not exposed. Properly protect work against damage by weather and other trades. Damaged surfaces shall be restored to original condition. Debris produced from this work shall be removed daily from premises. All exposed electrical conduit and equipment in finished areas shall be painted to match adjacent finishes. Touch up scratched or marred surfaces of panelboards, protective devices and similar electrical apparatus prior to applying finish coats of paint to equipment. All material, whether exposed or concealed, shall be firmly and adequately held in place. Make all connections tight and recheck all panel legs just prior to final inspection.

SUPPORT: Support and fasten all conduits, equipment, etc. securely in place. Secure and adjust hangers and supports to keep conduits in alignment, to carry the weight of the conduits without deflection or sag. Inserts in masonry shall be lead or plastic types install in drilled holes. Wooden plugs, chains, straps, or wire hangers are prohibited. Provide steel supports, frames, bracing, etc., incidental to this scope of work. Refer to 2017 NEC for further direction.

CUTTING/REPAIR: The Electrical Contractor shall provide all cutting and repairing of walls, floors, and ceiling necessary for the installation of work. Set sleeves for conduit as building construction progresses. Exterior walls shall not be pierced. Any cutting of structural members or finished work shall prior approval of architect/structural engineer. Any piping, ductwork, conduits, etc., damaged in any way, by this contractor shall be repaired or replaced at no additional expense to the owner.

IDENTIFICATION: All equipment installed under this contract shall be identified with an engraved laminated phenolic plastic nameplate, white core, and black surface, screwed in place. All generator equipment installed under this contract shall be identified with an engraved laminated phenolic plastic nameplate, white core, and red surface, screwed in place. Labels created by a device similar to a "tapewriter" are not acceptable. All wiring shall be marked with Brady Self-Sticking wire markers. All wiring shall be color coded with no exceptions. Conductors no. 4 and larger may be identified with 3" (minimum) bands of proper color plastic tape near each termination.

FINAL COMPLETION: Upon completion of the work, demonstrate the installation make such tests as may be required to satisfy the architect/engineer and owner that work is installed in accordance with the drawings, specifications, and instructions. Provide a certificate of inspection from the local or state authorities having jurisdiction over the work.

WARRANTY: All equipment and workmanship shall be guaranteed for a period of one year from the date of acceptance. Faulty workmanship and defective materials shall be corrected immediately.

PART TWO - MATERIALS AND EQUIPMENT

All materials and equipment shall be new and of the highest quality in the class specified except for owner supplied equipment. All materials and equipment shall be listed and labeled as required by Where trade names are mentioned they are given as a reference to the quality and performance of the apparatus required. Other brands may be used if approved in writing by the Engineer and if their construction, performance, and efficiency is equal to that specified. The contractor shall submit a complete list of any proposed alternate materials and equipment for use in this project to the Engineer within 10 days following the award of the contract. If such a list is not submitted, the Electrical Contractor shall supply the materials and equipment as specified or (if not specified) as directed by the engineer.

CONDUIT: Conduits run underground or in poured concrete shall be galvanized rigid steel conduit or Schedule 40 PVC. Exposed PVC conduit shall not be permitted. Sleeves and openings shall be provided as required to accommodate passage of conduits, etc. to be installed. Sleeve shall be no. 16 galvanized sheet steel, rigidly supported. Provide all hangers required to support conduits, pull boxes, etc. Supports improperly installed shall be removed and replaced at no additional expense to the owner. Refer to 2017 NEC for further direction.

CONDUCTORS: Conductors may be copper or aluminum, size as indicated on the drawings; minimum size no. 12 AWG, color coded; Type THHN for branch circuits, Type THW or THHN/THWN for feeders; Type USE for underground service conductors. No. 12 wire and smaller shall be solid; No. 8 and larger wire shall be stranded (no exceptions). All conductors rated 50A or less shall be copper. All conductors, with the exception of control wiring and switch legs, shall be No. 12 or larger. Switch legs may be No. 14.

WIRING METHODS: Type MC and EMT are allowed wiring methods.

PANELBOARDS: Panelboards shall be dead front, safety type, and shall be the thermal magnetic circuit breaker type. Refer to the panel schedule in the drawing for the number of branch circuits, ampere ratings, number of poles, main breakers, etc. Circuits shall be connected to the panel as indicated in the panel schedule. Provide solderless type connectors on main and load side of branch circuits. Provide a circuit directory card indicating device and areas on each circuit. Panelboard shall be equivalent to Square D type "NQOD" rated at the voltage specified in the panel schedule.

SAFETY SWITCHES: Safety switches shall be heavy-duty type, fusible, horsepower rated, 250 volts, quick-break mechanism, listed and labeled per 2017 NEC.

FUSES: Fuses shall be standard 2017 NEC cartridge type, dual element, equivalent to Fusetron. All fuses are to be sized according to manufacturer's recommendations.

OUTLET, JUNCTION AND PULL BOXES: Outlet boxes shall be sized in accordance with the 2017 NEC. Plastic boxes are not acceptable.



TOGGLE SWITCHES: Toggle switches shall be rated 20 Amps, 120/277 Volts, listed and labeled per 2017 NEC, verify color with owner.

RECEPTACLES: Receptacles shall be grounding type with grounding connection through extra pole permanently connected to panelboard ground bus via green conductor, listed and labeled per 2017 NEC, verify color with owner. Other colors may be substituted for special outlets that are not normally visible or as otherwise noted on plans.

LIGHTING: The lighting system shall be provided complete, including all luminaries, lamps, supporting members, hangers, etc. All light fixture must be independently supported from the building structure. Refer to the drawings for luminaire type, description, and performance specification. All related parts required for a complete installation shall be provided whether or not specifically mentioned.

LIGHTING CONTROLS: Electrical Contractor to provide complete system and ensure proper operation.

ARC-FLASH: Electrical Contractor is to provide Arc-Flash Analysis/Report prepared by VA licensed engineer and label all new electrical panels. Service entrance to be labeled with available fault current.



ELECTRICAL NOTES:

- ELECTRICAL CONTRACTOR MUST VERIFY AVAILABLE FAULT CURRENT WITH LOCAL POWER COMPANY TO ENSURE PROPER SIZING OF EQUIPMENT.
- ALL RECEPTACLES WITHIN 6 FT OF SINK MUST BE GROUND FAULT CIRCUIT INTERRUPT PROTECTED.
- WHERE ELECTRICAL WORK PENETRATES FIRE RATED BARRIERS (WALLS, FLOORS AND CEILINGS) SEAL OPENING AROUND ELECTRICAL WORK WITH U.L. LISTED FIRE STOPPING MATERIAL TO MAINTAIN THE FIRE RATING OF THE BARRIER.
- RECEPTACLES OR OTHER DEVICES THAT MUST BE RECESSED INTO FIRE RATED PARTITIONS MUST BE OFFSET TO PREVENT A THROUGH PENETRATION.
- MEETING/CONFERENCE ROOMS SHALL COMPLY WITH NEC 2017 SECTION 710.71.
- ELECTRICAL CONTRACTOR IS TO VERIFY ELECTRICAL LOADS, LOCATIONS, DISCONNECTING MEANS, AND REQUIREMENTS WITH MECHANICAL AND PLUMBING CONTRACTORS.
- CONNECT ALL EXIT AND EMERGENCY LIGHTS TO NEAREST UNSWITCHED LIGHTING CIRCUIT IN THE AREA IT SERVES.
- ELECTRICAL CONTRACTOR TO PROVIDE ACCURATE PANEL SCHEDULES AT COMPLETION OF PROJECT, IDENTIFY ROOMS AND DEVICES SERVED.
- LABEL ALL DEVICES WITH CIRCUIT NUMBERS FOR EASE OF MAINTENANCE INCLUDING RECEPTACLES AND LIGHT FIXTURES.
- ELECTRICAL CONTRACTOR IS TO COORDINATE LOCATIONS AND REQUIREMENTS OF ALL TELE/DATA WITH OWNER.
- ELECTRICAL CONTRACTOR IS TO PROVIDE ELECTRICAL CONNECT TO GENERATOR BLOCK HEATER. CONNECT TO CIRCUIT P1-49.
- ELECTRICAL CONTRACTOR IS TO PROVIDE ELECTRICAL CONNECT TO GENERATOR BATTERY CHARGER. CONNECT TO CIRCUIT P1-51.
- ELECTRICAL CONTRACTOR SHALL COORDINATE ALL LIGHT FIXTURE SPECIFICATIONS & ASSOCIATED TRIMS/DRIVERS WITH THE APPLICATION. MODIFY SPECIFICATIONS AS REQUIRED AND OBTAIN OWNER APPROVAL.
- CONTROL SCHEME FOR VACANCY SENSORS IS MANUAL ON/ AUTO OFF WITH MANUAL OVERRIDE SWITCH FOR OFF. COORDINATE TIME-OUT OF OCCUPANCY SENSORS WITH OWNER.
- ELECTRICAL CONTRACTOR IS TO INSTALL MEDICAL FACILITIES GRADE WIRING IN ALL DESIGNATED PATIENT CARE AREAS; CABLE TYPE HFC OR EQUIVALENT SHALL BE USED. METAL CONDUITS SHALL BE 1/2" OR GREATER. WIRE IN CONDUITS SHALL BE CABLE TYPE THHN.
- ALL ELECTRICAL MATERIALS, DEVICES, APPLIANCES, AND EQUIPMENT SHALL BE LABEL-LISTED BY A VIRGINIA APPROVED THIRD PARTY TESTING AGENCY.
- ELECTRICAL EQUIPMENT, CONDUCTORS AND TERMINATIONS SHALL BE COORDINATED AND COMPLY WITH NEC ARTICLE 110-14(C).
- ALL RECEPTACLES LOCATED OUTDOORS, IN DAMP OR WET LOCATIONS, OR OTHERWISE SUBJECT TO NON-CONTROLLED TEMPERATURE AND HUMIDITY ENVIRONMENT SHALL BE WEATHER RESISTANT GFCI TYPE.
- A 120V, DUPLEX RECEPTACLE SHALL BE INSTALLED WITHIN 25 FT OF ALL HEATING, AIR CONDITIONING, AND REFRIGERATION EQUIPMENT.
- VERIFY LOCATIONS OF ANY AIR RETURN PLENUMS. ELECTRICAL CONTRACTOR IS TO PROVIDE PLENUM-RATED CABLING AND WIRING METHODS IN THESE AREAS.
- PROVIDE AND INSTALL TAMPER-RESISTANT RECEPTACLES IN ALL LOCATION REQUIRED BY NEC SECTION 406.12.

2018 APPENDIX B BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS ELECTRICAL DESIGN ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance: Energy Code Performance Prescriptive
ASHRAE 90.1 Performance Prescriptive

Lighting schedule (each fixture type)
lamp type required in fixture LED 1
number of lamps in fixture 1
ballast type used in the fixture Driver 1
number of ballasts in fixture 1
total wattage per fixture 21,29.31,32,39,51,63
total interior wattage specified vs allowed 4.4kw/VS-5.2kw
total exterior wattage specified vs allowed N/A/VS-N/A

Additional Efficiency Package Options
(When using the 2018 IECC; not required for ASHRAE 90.1)
 C406.2 More Efficient HVAC Equipment Performance
 C406.3 Reduced Lighting Power Density
 C406.4 Enhanced Digital Lighting Controls
 C406.5 On-Site Renewable Energy
 C406.6 Dedicated Outdoor Air System
 C406.7 Reduced Energy Use in Service Water Heating

DESIGNER STATEMENT:

DESIGNER STATEMENT:
To the best of my knowledge and belief, the design of this building complies with the electrical system and equipment requirements of the IECC.

SIGNED: *J Wade White, Jr.*
NAME: J Wade White, Jr.
TITLE: Electrical Engineer

FIRE ALARM SYSTEMS LEGEND

- [P] PULL STATION
- [SD] SMOKE DETECTOR
- [S] WALL MOUNTED STROBE WITH CANDELA RATING
- [H/S] WALL MOUNTED HORN/STROBE WITH CANDELA RATING
- [FACP] FIRE ALARM PANEL
- [ANN] FIRE ALARM ANNUNCIATOR PANEL

FIRE ALARM WIRING NOTE:

- FIRE ALARM INSTALLER IS TO COORDINATE WITH FIRE MARSHALL ON REQUIRED DOCUMENTATION NEEDED.
- FIRE ALARM INSTALLER TO VERIFY LOCATION OF FIRE ALARM PANEL & ANNUNCIATOR PANEL.
- VERIFY WITH MECHANICAL DRAWINGS FOR DETERMINATION OF UNITS TO RECEIVE DUCT SMOKE DETECTORS. MECHANICAL CONTRACTOR IS TO PROVIDE AND INSTALL IN HVAC UNIT, THEN FIRE ALARM INSTALLER SHOULD WIRE DETECTORS INTO SYSTEM.
- FIRE ALARM STROBE LIGHTS SHALL BE PROVIDED AS REQUIRED BY NFPA 72.

ELECTRICAL & FIRE ALARM SHEET LISTING


1	E-0.1	ELECTRICAL COVER SHEET
2	E-0.2	ELECTRICAL RISER DIAGRAM & ELECTRICAL SCHEDULES
3	ED-1	ELECTRICAL DEMO PLAN
4	E-1.0	OVERALL LIGHTING PLAN
5	E-1.1	ENLARGED LIGHTING PLANS
6	E-1.2	ENLARGED LIGHTING PLAN
7	E-2.0	OVERALL POWER & FIRE ALARM PLAN
8	E-2.1	ENLARGED POWER & FIRE ALARM PLANS
9	E-2.2	ENLARGED POWER & FIRE ALARM PLAN
10	E-3	ROOF HVAC ELECTRICAL & POWER PLAN

LIGHTING SYMBOLS LEGEND

- [Symbol] 2X2 LAY-IN FLAT PANEL LIGHT FIXTURE
- [Symbol] 2X4 LAY-IN FLAT PANEL LIGHT FIXTURE
- [Symbol] 2X4 LAY-IN FLAT PANEL LIGHT FIXTURE, CONNECTED TO NIGHT LIGHT BRANCH CIRCUIT
- [Symbol] 4' PENDANT MOUNTED LINEAR LED LIGHT FIXTURE
- [Symbol] EXHAUST FAN (BY MC; WIRED BY EC)
- [Symbol] WALL MOUNTED EXIT/EMERGENCY COMBO LIGHT FIXTURE WITH BATTERY BACK UP LED
- [Symbol] CEILING MOUNTED SINGLE-FACED EXIT LIGHT FIXTURE WITH BATTERY BACK UP LED
- [Symbol] CEILING MOUNTED DOUBLE-FACED EXIT LIGHT FIXTURE WITH BATTERY BACK UP LED
- [Symbol] WALL MOUNTED EMERGENCY LIGHT FIXTURE WITH BATTERY BACK UP LED
- [Symbol] WALL MOUNTED EXTERIOR EGRESS EMERGENCY LIGHT FIXTURE BATTERY BACKED UP BY INTERIOR EXIT/EMERGENCY COMBO LED
- [Symbol] 6" RECESSED MOUNTED LED CAN LIGHT FIXTURE
- [Symbol] SINGLE POLE SWITCH
- [Symbol] THREE-WAY SWITCH
- [Symbol] SINGLE POLE DIMMER SWITCH (MATCH DIMMER TO LIGHT SOURCE CONTROLLED)
- [Symbol] THREE-WAY DIMMER SWITCH (MATCH DIMMER TO LIGHT SOURCE CONTROLLED)
- [Symbol] SINGLE POLE/OCCUPANCY SENSOR SWITCH (EQUIVALENT TO SENSOR SWITCH: WSD PDT WH)
- [Symbol] MOTOR RATED SWITCH
- [Symbol] CEILING MOUNTED DUAL TECHNOLOGY OCCUPANCY SENSOR (EQUIVALENT TO SENSOR SWITCH: CM PDT 8)
- [Symbol] (EQUIVALENT TO SENSOR SWITCH POWER PACK: PP20)
- [Symbol] DIGITAL TIME CLOCK (VERIFY LOCATION). INTERMATIC ET279C. (GRANGER 5U787).

POWER SYMBOLS LEGEND

- [Symbol] WALL MOUNTED DUPLEX OUTLET
- [Symbol] WALL MOUNTED GROUND FAULT CIRCUIT INTERRUPT DUPLEX OUTLET
- [Symbol] WALL MOUNTED QUAD OUTLET
- [Symbol] WALL MOUNTED GROUND FAULT CIRCUIT INTERRUPT QUAD OUTLET
- [Symbol] JUNCTION BOX (VERIFY REQUIREMENTS)
- [Symbol] RECESSED WALL MOUNTED DUPLEX OUTLET/TV BOX (EQUIVALENT TO LEGRAND TVM)(VERIFY BOX CONFIGURATION WITH OWNER)
- [Symbol] WALL MOUNTED DATA/VOICE BACKBOX 3/4" STUBBED ABOVE CEILING WITH PULL STRING (VERIFY REQUIREMENTS)
- [Symbol] SAFETY DISCONNECT SWITCH (FUSED AS REQUIRED) (AMPS/VOLTS/POLES/FUSE/NEMA RATING)
- [Symbol] DEDICATED CIRCUIT
- [Symbol] DEVICE MOUNTED ABOVE FINISHED COUNTER (VERIFY FINAL HEIGHT)
- [Symbol] TAMPER-RESISTANT
- [Symbol] WEATHER PROOF
- [Symbol] EXISTING TO REMAIN
- [Symbol] EXISTING DEVICE TO BE REMOVED



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WM Architects/Planners, Inc. ©2021 WM Architects. These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status: ISSUED FOR CONSTRUCTION

Revision No (If Any): Revision Date:

Project No: 2021-003 Current Date: 10/25/21

Drawing Name:

Electrical Cover Sheet

E-0.1



BECI Project No: 5811

GENERAL DEMOLITION NOTES:

1. THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL LABOR, MATERIALS, AND EQUIPMENT, AND PERFORM ALL OPERATIONS NECESSARY FOR THE DEMOLITION OF EXISTING ELECTRICAL WORK TO MEET THE INTENT OF, AND AS INDICATED ON THE DEMOLITION DRAWINGS. SPECIFIC ITEMS AND MATERIALS MAY OR MAY NOT BE ADDRESSED IN SPECIFICATIONS AND DRAWINGS.
2. ALL WORK SHALL BE IN ACCORDANCE WITH THE CURRENT STATE BUILDING CODE, LOCAL CODES, NFPA, CURRENT NEC AND ALL OTHER APPLICABLE CODES AND REQUIREMENTS OF THE LOCAL INSPECTOR. THESE CODE STANDARDS ARE NOT ACCEPTABLE ALTERNATIVES TO REDUCE THE STANDARDS OR REQUIREMENTS OUTLINED IN THESE PLANS AND SPECIFICATIONS. ALL APPLICABLE "OSHA" REGULATIONS MUST BE FOLLOWED WHILE PERFORMING THIS WORK.
3. BEFORE SUBMITTING BID, THE ELECTRICAL CONTRACTOR SHALL BE RESPONSIBLE FOR VISITING THE SITE TO VERIFY/EXAMINE THE EXACT EXTENT OF EXISTING CONDITIONS.
4. THE ELECTRICAL DEMOLITION DRAWINGS ARE BASED ON EXISTING PLANS AND FIELD INVESTIGATION PRIOR TO DEMOLITION. LOCATIONS OF CONCEALED ELECTRICAL CONDUIT AND EQUIPMENT CAN NOT BE VERIFIED.
5. THE ELECTRICAL DEMOLITION DRAWINGS INDICATE THE GENERAL EXTENT OF THE EXISTING ELECTRICAL SYSTEMS TO BE REMOVED OR RELOCATED. ALL COMPONENTS ASSOCIATED WITH SYSTEMS AND EQUIPMENT TO BE REMOVED OR RELOCATED MAY NOT BE SPECIFICALLY INDICATED BUT SHALL BE REMOVED. ASSOCIATED ELECTRICAL COMPONENTS TO BE REMOVED INCLUDES, BUT IS NOT LIMITED TO, THE FOLLOWING ITEMS: HANGERS, WIRING, CABLING, CONDUIT, BOXES, STARTERS, DISCONNECTS, SWITCHES.
6. DISCONNECT EXISTING TO BE REMOVED OR EXISTING TO BE RELOCATED CONDUIT, WIRING, CABLING, AND EQUIPMENT AS INDICATED ON ELECTRICAL DEMOLITION DRAWINGS. UNUSED CONDUIT AND WIRING SHALL BE REMOVED BACK TO THE SOURCE FOR THE UNUSED SEGMENT. UNLESS SPECIFICALLY INDICATED, NO EQUIPMENT, MATERIALS OR ASSOCIATED COMPONENTS SHALL BE ABANDONED IN PLACE.
7. EXERCISE EXTREME CARE WHEN WORKING AROUND EXISTING WORK TO REMAIN. ANY DAMAGE TO EXISTING TO REMAIN OR EXISTING TO BE RELOCATED MATERIALS AND EQUIPMENT SHALL BE CORRECTED OR REPLACED TO THE SATISFACTION OF THE OWNER AT NO ADDITIONAL COST.
8. WHERE EXISTING FLOORS, WALLS AND ROOFS MUST BE CUT OR ARE DAMAGED DURING REMOVAL OR RELOCATION OF ELECTRICAL WORK, PATCH THE CUT OR DAMAGED AREAS TO MATCH ADJACENT CONSTRUCTION.
9. ELECTRICAL SYSTEMS ASSOCIATED WITH OCCUPIED PORTIONS OF THE BUILDING SHALL BE KEPT IN OPERATION AS MUCH AS POSSIBLE. WHEN REQUIRED, OUTAGES SHALL BE SCHEDULED AND APPROVED IN ADVANCE BY THE OWNER. OUTAGE DURATION SHALL BE KEPT TO A MINIMUM. WHERE NECESSARY, PROVIDE TEMPORARY CONNECTIONS AS REQUIRED TO MAINTAIN SERVICE.
10. THE CONTINUITY OF ALL EXISTING CONDUITS AND FEEDERS SERVICING AREAS TO REMAIN SHALL BE MAINTAINED. MODIFY THE EXISTING CIRCUITS IF REQUIRED IN ORDER TO MAINTAIN THE EXISTING CIRCUITRY.
11. ALL ABANDONED CIRCUITRY, ELECTRICAL BOXES, AND CONDUIT SHALL BE DEMOLISHED.

ELECTRICAL DEMO KEYED NOTES:

1. UNLESS OTHERWISE INDICATED, REMOVE ALL EXISTING EXIT SIGNS, EMERGENCY LIGHTING FIXTURES, LIGHTING FIXTURES, & ASSOCIATED CONTROLS IN THIS SPACE.
2. UNLESS OTHERWISE INDICATED, REMOVE ALL EXISTING RECEPTACLES, EQUIPMENT CONNECTIONS, AND DATA OUTLETS IN THIS SPACE.
3. UNLESS OTHERWISE INDICATED, ALL ELECTRICAL DEVICES ARE EXISTING TO REMAIN IN THIS ROOM.
4. EXISTING PANEL A TO BE DEMOLISHED. REFER TO DEMO ELECTRICAL RISER DIAGRAM FOR ADDITIONAL INFORMATION.
5. EXISTING PANEL TO REMAIN.
6. DEMOLISH EXISTING SERVICE ENTRANCE FEEDER SERVING EXISTING PANEL OMP. REMOVE GROUNDING ELECTRODE CONDUCTOR CONNECT TO EXISTING GROUNDING ELECTRODE. REMOVE NEUTRAL-GROUND BONDING JUMPER. REFER TO DEMO ELECTRICAL RISER DIAGRAM FOR ADDITIONAL INFORMATION.



Renovations of
**Baywood
Technology &
Community Center**
247 Grammer Lane
Galax, VA. 24333




These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WMA Architects/Planners, Inc.
©2021 WMA Architects.
These drawings, as instruments of service, remain the property of the Architect.
Unauthorized use or reproduction is forbidden.

Project Status:
ISSUED FOR CONSTRUCTION
Revision No (if any): Revision Date:
Project No: Current Date:
2021-003 10/25/21
Drawing Name:

Electrical Demo Plan
ED-1
BECI Project No: 5811



OVERALL LIGHTING PLAN
1 E-1.0 SCALE: 1/8" = 1' - 0"

Renovations of
Baywood Technology & Community Center
247 Grammer Lane
Galax, VA. 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WMA Architects/Planners, Inc.
©2021 WMA Architects.
These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status:
ISSUED FOR CONSTRUCTION



Revision No (if any)	Revision Date
Project No: 2021-003	Current Date: 10/25/21

Drawing Name:
Overall Lighting Plan


Drawing No:
E-1.0

BECI Project No: S811

- ELECTRICAL KEYED NOTES:**
- UNLESS OTHERWISE INDICATED, ALL ELECTRICAL DEVICES EXISTING TO REMAIN IN THIS ROOM.
 - CORRIDOR LIGHTING FIXTURES ARE CONTROLLED VIA DIGITAL TIME CLOCK LOCATED IN STORAGE 249 AND SINGLE POLE SWITCH IN RECEPTION 201.
 - VERIFY EXACT LOCATION OF DIGITAL TIME CLOCK IN FIELD.




ENLARGED
EXIT, EMERGENCY,
& LIGHTING PLAN
E-1.1 SCALE: 1/4" = 1' - 0"



ENLARGED
EXIT, EMERGENCY,
& LIGHTING PLAN
E-1.1 SCALE: 1/4" = 1' - 0"


Renovations of
**Baywood
Technology &
Community Center**
247 Grammer Lane
Galax, VA. 24333





ENLARGED
EXIT, EMERGENCY,
& LIGHTING PLAN
E-1.2 SCALE: 1/4" = 1' - 0"

- ⊙ ELECTRICAL KEYED NOTES:
1. UNLESS OTHERWISE INDICATED, ALL ELECTRICAL DEVICES ARE EXISTING TO REMAIN IN THIS ROOM.
 2. CORRIDOR LIGHTING FIXTURES ARE CONTROLLED VIA DIGITAL TIME CLOCK LOCATED IN STORAGE 249 AND SINGLE POLE SWITCH IN RECEPTION 201.



Renovations of
**Baywood
Technology &
Community Center**
247 Grammer Lane
Galax, VA. 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WMA Architects/Planners, Inc.
©2021 WMA Architects.
These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.


Project Status:
ISSUED FOR CONSTRUCTION

Revision No (if any): Revision Date:

Project No: Current Date:
2021-003 10/25/21

Drawing Name:

Enlarged Lighting Plan
Drawing No:
E-1.2
BECI Project No: 5811



OVERALL
 POWER & FIRE
 ALARM PLAN
 1
 E-2.0 SCALE: 1/8" = 1' - 0"

Renovations of
**Baywood
 Technology &
 Community Center**
 247 Grammer Lane
 Galax, VA. 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WM2A Architects/Planners, Inc.
 ©2021 WM2A Architects.
 These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status:

ISSUED FOR CONSTRUCTION

Revision No (if any): Revision Date:

Project No: 2021-003 Current Date: 10/25/21

Drawing Name:

Overall Power & Fire Alarm Plan

Drawing No:



E-2.0

BECI Project No: S811


PATIENT CARE AREAS	
EXAM 1	(104)
EXAM 2	(105)
EXAM 3	(106)
EXAM 4	(107)

⊖ ELECTRICAL KEYED NOTES:


1. PROVIDE MANUFACTURER'S RECOMMENDED CONDUIT AND CONTROL WIRING BETWEEN INTERIOR AIR HANDLER (MAHU) AND EXTERIOR HEAT PUMP (MSHP).
2. INTERIOR AIR HANDLER (MAHU) POWERED FROM EXTERIOR HEAT PUMP (MSHP).
3. UNLESS OTHERWISE INDICATED, ALL ELECTRICAL DEVICES ARE EXISTING TO REMAIN IN THIS ROOM.
4. COORDINATE RECEPTACLE LOCATION WITH MICROWAVE.
5. CONFIRM POWER REQUIREMENTS FOR DATA CLOSET WITH OWNER.
6. PROVIDE MANUFACTURER'S RECOMMENDED CONDUIT, CONTROL WIRING, AND POWER WIRING BETWEEN SECURITY GATE AND SECURITY GATE CONTROLS. VERIFY LOCATION OF SECURITY GATE AND SECURITY GATE CONTROLS IN FIELD.
7. VERIFY LOCATION WITH OWNER IN FIELD.
8. PROVIDE GENERATOR WITH WEATHER-PROOF ENCLOSURE AND SUB-BASE FUEL TANK SIZED FOR 12 HOURS OF FUEL AT 100% RATED LOAD.
9. 1200A, NEMA-3R, S.E. RATED, FUSED SAFETY SWITCH (SERVICE DISCONNECT). REFER TO ELECTRICAL RISER DIAGRAM FOR ADDITIONAL INFORMATION.
10. CONNECT BRANCH CIRCUIT INDICATED TO AUTOMATIC FAUCET POWER SUPPLY (PROVIDED BY OTHERS). COORDINATE LOCATION OF AUTOMATIC FAUCET POWER SUPPLY WITH PLUMBING CONTRACTOR IN FIELD. ELECTRICAL CONTRACTOR SHALL PROVIDE MOTOR RATED SWITCH AND ALL CONDUIT AND WIRING TO THE AUTOMATIC FAUCET POWER SUPPLY.



ENLARGED
HVAC ELECTRICAL, POWER,
& FIRE ALARM PLAN
1
E-2.1 SCALE: 1/4" = 1' - 0"




ENLARGED
HVAC ELECTRICAL, POWER,
& FIRE ALARM PLAN
2
E-2.1 SCALE: 1/4" = 1' - 0"



ENLARGED
HVAC ELECTRICAL, POWER,
& FIRE ALARM PLAN
E-2.2 SCALE: 1/4" = 1' - 0"

- ELECTRICAL KEYED NOTES:**
1. PROVIDE MANUFACTURER'S RECOMMENDED CONDUIT AND CONTROL WIRING BETWEEN INTERIOR AIR HANDLER (MAHU) AND EXTERIOR HEAT PUMP (MSHP).
 2. INTERIOR AIR HANDLER (MAHU) POWERED FROM EXTERIOR HEAT PUMP (MSHP).
 3. UNLESS OTHERWISE INDICATED, ALL ELECTRICAL DEVICES ARE EXISTING TO REMAIN IN THIS ROOM.
 4. CONNECT BRANCH CIRCUIT INDICATED TO AUTOMATIC FAUCET POWER SUPPLY (PROVIDED BY OTHERS). COORDINATE LOCATION OF AUTOMATIC FAUCET POWER SUPPLY WITH PLUMBING CONTRACTOR IN FIELD. ELECTRICAL CONTRACTOR SHALL PROVIDE MOTOR RATED SWITCH AND ALL CONDUIT AND WIRING TO THE AUTOMATIC FAUCET POWER SUPPLY.



Renovations of
**Baywood
Technology &
Community Center**
247 Grammer Lane
Galax, VA. 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.

© 2021, WMA Architects/Planners, Inc.
© 2021 WMA Architects.
These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.


Project Status:
ISSUED FOR CONSTRUCTION
Revision No (if any): Revision Date:

Project No: Current Date:
2021-003 10/25/21


Drawing Name:
**Enlarged Power &
Fire Alarm Plan**
Drawing No:
E-2.2

BECI Project No: 5811

⊖ ELECTRICAL KEYED NOTES:
 1. MOUNT INDEPENDENTLY OF MECHANICAL ENCLOSURE.



ROOF
 HVAC ELECTRICAL
 & POWER PLAN
 1
 E-3 SCALE: 1/8" = 1' - 0"



Renovations of
**Baywood
 Technology &
 Community Center**
 247 Grammer Lane
 Galax, VA, 24333



These drawings convey certain contractual information through the use of color. Do NOT use drawings printed in black and white or grayscale.
 © 2021, WMA Architects/Planners, Inc.
 © 2021 WMA Architects.
 These drawings, as instruments of service, remain the property of the Architect. Unauthorized use or reproduction is forbidden.

Project Status:	
ISSUED FOR CONSTRUCTION	
Revision No (if any):	Revision Date:
Project No: 2021-003	Current Date: 10/25/21
Drawing Name: Roof HVAC Electrical & Power Plan	
Drawing No: E-3	
BECI Project No: 5811	